



RLDEWS24

- Screw connection
- Mounting flange position 3
- white LED
- 24 VAC/DC

Data

Ordering data

Product type description	RLDEWS24
Article number (order number)	101195136
EAN (European Article Number)	4030661487366
eCl@ss number, version 9.0	27-37-12-09
eCl@ss number, version 11.0	27-37-12-09
eCl@ss number, version 12.0	27-37-12-09
ETIM number, version 7.0	EC000204
ETIM number, version 6.0	EC000204

Approvals - Standards

Certificates	cURus EAC
--------------	--------------

General data

Standards	EN IEC 60947-1 EN IEC 62061 EN IEC 60947-5-1 EN IEC 60947-5-3 EN IEC 60947-5-5 EN IEC 60204-1
Installation conditions (mechanical)	arbitrarily
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	23 g

General data - Features

Integral system diagnostics, general	Yes
--------------------------------------	-----

Mechanical data

Installation instructions	pluggable
Mounting flange position	3

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Terminal designations	EN 50005 EN 50013
Cable section, minimum	0.5 mm ² , rigid 0.5 mm ² , flexible
Cable section, maximum	2.5 mm ² , rigid 1.5 mm ² , flexible
Tightening torque of Clips	1 Nm

Mechanical data - Dimensions

Length	46 mm
Width	10 mm
Depth	45 mm

Ambient conditions

Degree of protection of clips or terminals	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+75 °C

Ambient conditions - Insulation values

Rated insulation voltage U_i	440 V
--------------------------------	-------

Status indication

Colour of the LED	White
Note (LED switching conditions display)	Supply voltage U_B : 24 VAC/DC

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 11:20