



EDTRT

Data

Ordering data

Product type description	EDTRT
Article number (order number)	101006233
EAN (European Article Number)	4030661484754
eCl@ss number, version 9.0	27-37-12-10
eCl@ss number, version 11.0	27-37-12-10
eCl@ss number, version 12.0	27-37-12-10
ETIM number, version 7.0	EC000221
ETIM number, version 6.0	EC000221

Approvals - Standards

Certificates	cULus CCC
--------------	--------------

General data

Standards	EN IEC 60947-1 EN IEC 62061 EN IEC 60947-5-1 EN IEC 60947-5-3 EN IEC 60947-5-5 EN IEC 60204-1
Versions	Embeddable button - Front plate mounting
Design	Round
Installation conditions (mechanical)	arbitrarily
Sealing type	Membrane Lip gaskets Form seals
Material of the operators	Aluminium
Material of the front ring	Aluminium
Colour of the operating element	Red
Colour of the front ring	Silver
Gross weight	35 g

General data - Features

Mounting flange	Yes
Probing possible	Yes
Fully insulated	Yes

Mechanical data

Unlocking	without
Mechanical life, minimum	10,000,000 Operations
Actuating stroke	4 mm
Actuating force, approx.	1.5 N
Mounting	mounting flange
Tightening torque of the screw	0.6 Nm

Mechanical data - Dimensions

Height	14 mm
--------	-------

Length x Width x Height	Mounting hole Ø: 22 mm
Diameter total	29.5 mm
Diameter of touch surface	23 mm
Diameter of the front ring	29.5 mm
Diameter hole	22.3 mm
Diameter hole, with tolerance indication	22.3 + 0.4 mm
Thickness, of the front panel, minimum	1 mm
Thickness of the front panel, maximum	6 mm
Spacing	40 x 50 mm

Ambient conditions

Degree of protection	IP65
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C

Electrical data

Switching frequency	1,000 /h
---------------------	----------

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 09:46