



IFL 50-385-10/01D

- 3 Cable entry M 20 x 1.5
- Thermoplastic enclosure
- DC 2-wire
- Double-insulated
- Wiring compartment
- Design 385

Data

Ordering data

Product type description	IFL 50-385-10/01D
Article number (order number)	101126029
EAN (European Article Number)	4030661277691
eCl@ss number, version 9.0	27-27-01-01
eCl@ss number, version 11.0	27-27-01-01
ETIM number, version 7.0	EC002714
ETIM number, version 6.0	EC002714

Approvals - Standards

Certificates	CCC
--------------	-----

General data

Standards	EN IEC 60947-5-2 DIN VDE 0660-208
Housing construction form	Block
Installation conditions (mechanical)	not flush
Enclosure material	Plastic

Gross weight	378 g
--------------	-------

General data - Features

Integral system diagnostics, status	Yes
Number of cable wires	2

Mechanical data - Switching distances according EN IEC 60947-5-3

Nominal switching distance S_n	50 mm
----------------------------------	-------

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, maximum	2 x 1.5 mm ²

Mechanical data - Dimensions

Length of sensor	135 mm
Width of sensor	80 mm
Height of sensor	40 mm

Ambient conditions

Degree of protection	IP67
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C
Protection class	II

Electrical data

Voltage type	DC (direct current)
Operating voltage, minimum	10 V
Operating voltage, maximum	40 V
Operating current, minimum	0.01 mA

Operating current	200 mA
Switching element	NO contact or NC contact
Protection circuit integrated	inductive interference protection Protection against polarity reversal Surge protection Max. fuse rating
Switching frequency, approx.	50 Hz

Electrical data - Digital Output

Voltage drop U_d , maximum	5.5 V
Current at Voltage drop U_d	0.1 A
Design of control elements	Two-wire
Current leakage I_r , maximum	0.5 mA

Status indication

Note (Integral System Diagnostics, status)	yellow LED
---	------------

Note

Note (General)	Programmable by repositioning the plug-in jumper at the terminal screws Mounting angle HW 385-1 to simplify mounting available
----------------	---

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 11:41