



## V-SK8P-M12-S-G-0,25M-BK-2-X-A-4-69

### Data

#### Ordering data

|                               |                                    |
|-------------------------------|------------------------------------|
| Product type description      | V-SK8P-M12-S-G-0,25M-BK-2-X-A-4-69 |
| Article number (order number) | 103014812                          |
| EAN (European Article Number) | 4030661498713                      |
| eCl@ss number, version 9.0    | 27-06-03-11                        |
| eCl@ss number, version 11.0   | 27-06-03-11                        |
| eCl@ss number, version 12.0   | 27-06-03-11                        |
| ETIM number, version 7.0      | EC001855                           |
| ETIM number, version 6.0      | EC001855                           |

#### General data

|              |                    |
|--------------|--------------------|
| Standards    | EN IEC 61076-2-101 |
| Versions     | straight           |
| Gross weight | 41 g               |

#### General data - Features

|                           |         |
|---------------------------|---------|
| Halogen free              | Yes (1) |
| Cable drag chain suitable | Yes (1) |
| Number of cable wires     | 8       |

## Mechanical data

|                            |      |
|----------------------------|------|
| Tightening torque, maximum | 1 Nm |
|----------------------------|------|

## Mechanical data - Connection technique

|                              |                      |
|------------------------------|----------------------|
| Length of cable              | 0.25 m               |
| Wire cross-section           | 0.25 mm <sup>2</sup> |
| Cable diameter               | 5.9 mm               |
| Bending radius (fixed)       | 5 x Ø-cable          |
| Bending radius (repeated)    | 10 x Ø-cable         |
| Colour of the Cable mantle   | Black                |
| Material of the Cable mantle | PUR                  |

## Mechanical data - connector side A

|                        |                            |
|------------------------|----------------------------|
| Connector typ          | Female connector, M12      |
| Design                 | straight                   |
| Connector coding       | A                          |
| Connector latching     | Screw locking              |
| Material of the gland  | Metal, CuZn, nickel-plated |
| Material of the handle | Plastic, TPU               |
| Colour of the handle   | Black                      |

## Mechanical data - connector side B

|                        |                            |
|------------------------|----------------------------|
| Connector typ          | Male connector, M12        |
| Design                 | straight                   |
| Connector coding       | A                          |
| Connector latching     | Screw locking              |
| Material of the gland  | Metal, CuZn, nickel-plated |
| Material of the handle | Plastic, TPU               |
| Colour of the handle   | Black                      |

## Ambient conditions

|                                          |                      |
|------------------------------------------|----------------------|
| Degree of protection                     | IP67<br>IP69<br>IP65 |
| Ambient temperature, minimum (Connector) | -30 °C               |
| Ambient temperature, maximum (Connector) | +90 °C               |
| Temperature (fixed), minimum             | -50 °C               |
| Temperature (fixed), maximum             | +90 °C               |
| Temperature (repeated), minimum          | -30 °C               |
| Temperature (repeated), maximum          | +90 °C               |
| Temperature (drag chain), minimum        | -25 °C               |
| Temperature (drag chain), maximum        | +60 °C               |

## Electrical data

|                         |          |
|-------------------------|----------|
| Thermal test current    | 2 A      |
| Rated operating voltage | 30 V     |
| Operating current       | 2,000 mA |

## Pin assignment

|       |        |
|-------|--------|
| PIN 1 | White  |
| PIN 2 | Brown  |
| PIN 3 | green  |
| PIN 4 | yellow |
| PIN 5 | Grey   |
| PIN 6 | Pink   |
| PIN 7 | Blue   |
| PIN 8 | red    |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 08:06