



T4R 235-20Z

- 1 Cable entry M 20 x 1.5
- Metal enclosure
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- 30 mm x 63,5 mm x 30 mm
- Actuator heads can be repositioned by 4 x 90°
- Mounting details to EN 50047

Data

Ordering data

Product type description	T4R 235-20Z
Article number (order number)	101112912
eCl@ss number, version 9.0	27-27-06-01
eCl@ss number, version 11.0	27-27-06-01
eCl@ss number, version 12.0	27-27-06-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

General data

Standards	EN IEC 60947-5-1 EN ISO 13849-1 BG-GS-ET-15
Housing construction form	Norm construction design
Enclosure material	Metal, zinc die-cast
Material of the contacts, electrical	Silver
Gross weight	185 g

General data - Features

Number of auxiliary contacts	2
------------------------------	---

Safety classification

Standards	EN ISO 13849-1
-----------	----------------

Mission time	20 Year(s)
--------------	------------

Mechanical data

Actuating element	Roller plunger
-------------------	----------------

Mechanical life, minimum	20,000,000 Operations
--------------------------	-----------------------

Actuating force, minimum	9 N
--------------------------	-----

Positive break force, minimum	19 N
-------------------------------	------

Actuating speed, minimum	120 mm/min
--------------------------	------------

Actuating speed, maximum	1 m/s
--------------------------	-------

Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
------------------------	---

Note Bounce duration	Bounce duration in accordance with actuating speed
----------------------	--

Note (Switchover time)	Switchover time in accordance with actuating speed
------------------------	--

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
-------------	---------------------------

Cable section, minimum	0.75 mm ²
------------------------	----------------------

Cable section, maximum	2.5 mm ²
------------------------	---------------------

Note (Cable section)	All indications including the conductor ferrules.
----------------------	---

Mechanical data - Dimensions

Length of sensor	30 mm
------------------	-------

Width of sensor	30 mm
-----------------	-------

Height of sensor	103.5 mm
------------------	----------

Ambient conditions

Degree of protection	IP67 IP65
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation values

Rated insulation voltage U_i	500 V
Rated impulse withstand voltage U_{imp}	6 kV

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	50 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	Normally open contact (NO)
Switching principle	Slow action
Switching frequency	5,000 /h

Note

Note (General)	Switch with 2 NO contacts are not for security tasks
----------------	--

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 12:32