



RMLHGN

- high calotte
- for Ba9S LED's

Data

Ordering data

Product type description	RMLHGN
Article number (order number)	101188310
EAN (European Article Number)	4030661484464
eCl@ss number, version 9.0	27-37-12-11
eCl@ss number, version 11.0	27-37-12-11
eCl@ss number, version 12.0	27-37-12-11
ETIM number, version 7.0	EC000223
ETIM number, version 6.0	EC000223

General data

Standards	EN IEC 60947-1 EN IEC 62061 EN IEC 60947-5-1 EN IEC 60947-5-3 EN IEC 60947-5-5 EN IEC 60204-1
Versions	LED - Indicator light - Front plate mounting
Design	Round High calotte
Installation conditions (mechanical)	arbitrarily

Sealing type	Membrane Lip gaskets Form seals
Material of the dome	Plastic
Material of the front ring	Aluminium
Colour of the dome	Green
Colour of the front ring	Silver
Gross weight	45 g

General data - Features

Illuminable	Yes
Mounting flange	Yes
Fully insulated	Yes
Integral system diagnostics, general	No

Mechanical data

Mounting	Mounting flange ELM
Tightening torque of the screw	0.6 Nm

Mechanical data - Dimensions

Diameter total	39.5 mm
Height of the dome	11 mm
Diameter of the dome	22 mm
Diameter of the front ring	39.5 mm
Diameter hole	22.3 mm
Diameter hole, with tolerance indication	22.3 + 0.4 mm
Thickness, of the front panel, minimum	1 mm
Thickness of the front panel, maximum	6 mm
Spacing	40 x 50 mm

Ambient conditions

Degree of protection	IP65
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+75 °C

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 09:32