



EF303.1

- Screw connection
- Mounting flange position 1
- 11-12; 23-24 (Contact labelling)
- Suitable for EMERGENCY-OFF

Data

Ordering data

Product type description	EF303.1
Article number (order number)	101022137
EAN (European Article Number)	4250116201341
eCl@ss number, version 9.0	27-37-13-02
eCl@ss number, version 11.0	27-37-13-02
eCl@ss number, version 12.0	27-37-13-02
ETIM number, version 7.0	EC000041
ETIM number, version 6.0	EC000041

Approvals - Standards

Certificates	cULus
	CCC
	EAC

General data

Standards	EN IEC 60947-1 EN IEC 62061 EN IEC 60947-5-1 EN IEC 60947-5-3 EN IEC 60947-5-5 EN IEC 60204-1
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Contact labelling	11-12 23-24
Gross weight	20 g

General data - Features

Suitable for EMERGENCY-OFF	Yes
Number of normally closed (NC)	1
Number of normally open (NO)	1

Mechanical data

Installation instructions	pluggable
Mechanical life, minimum	10,000,000 Operations
Positive break travel	2 mm
Contact opening	3 mm
Note Bounce duration	Bounce duration at an Actuating speed of 100mm/s
Mounting flange position	1

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, minimum	0.5 mm ² , rigid 0.5 mm ² , flexible
Cable section, maximum	2.5 mm ² , rigid 1.5 mm ² , flexible
Note (Cable section)	All indications including the conductor ferrules.

Mechanical data - Dimensions

Length	46 mm
Width	10 mm
Depth	60 mm

Ambient conditions

Degree of protection of the switch rooms	IP40
Degree of protection of clips or terminals	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C
Resistance to shock	110 g / 4 ms
Resistant to vibration	Resistance to vibration: 20 g / 10...200 Hz

Ambient conditions - Insulation values

Rated insulation voltage U_i	400 V
--------------------------------	-------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	8 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	5 A
Suitable for low-voltages	$\geq 5 \text{ V} / \geq 3.2 \text{ mA}$
Switching element	NC contact, NO contact
Switching principle	Slow action
Bounce duration, maximum	5 ms
Switching frequency	1,200 /h

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 11:13