



EWTS321

- short toggle

Data

Ordering data

Product type description	EWTS321
Article number (order number)	101006375
EAN (European Article Number)	4030661520667
eCl@ss number, version 9.0	27-37-12-13
eCl@ss number, version 11.0	27-37-12-13
eCl@ss number, version 12.0	27-37-12-13
ETIM number, version 7.0	EC000222
ETIM number, version 6.0	EC000222

Approvals - Standards

Certificates	cULus CCC
--------------	--------------

General data

Standards	EN IEC 60947-1 EN IEC 62061 EN IEC 60947-5-1 EN IEC 60947-5-3 EN IEC 60947-5-5 EN IEC 60204-1
Versions	Toggle
Installation conditions (mechanical)	arbitrarily
Toggle	short
Sealing type	Membrane Lip gaskets Form seals
Material of the front ring	Aluminium
Material of the toggle	Plastic
Colour of the front ring	Silver
Colour of the handle	Grey
Gross weight	45 g

General data - Features

Probing possible	Yes
Fully insulated	Yes
Number of plunger	2
Number of switch positions	3

Mechanical data

Unlocking	Left: without rotating unlatcher Right: rotating unlatcher
Latching position	right
Touch position	left
Mechanical life, minimum	300,000 Operations
Switching angle, left	55 °
Switching angle, right	35 °
Mounting	mounting flange
Tightening torque of the screw	0.6 Nm

Mechanical data - Dimensions

Height	28 mm
Length x Width x Height	Mounting hole Ø: 22 mm
Diameter of the front ring	29.5 mm
Length of the handle	28 mm
Diameter hole	22.3 mm
Diameter hole, with tolerance indication	22.3 + 0.4 mm
Thickness, of the front panel, minimum	1 mm
Thickness of the front panel, maximum	6 mm
Spacing	50 x 50 mm

Ambient conditions

Degree of protection	IP65
Ambient temperature, minimum	+0 °C
Ambient temperature, maximum	+80 °C

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/08/2022, 09:48