

Filter Fan



Description

Order Number:	4023A3000
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54, Type 12, 3R
Optional:	Different housing colors available on request
Approvals:	CE, cURus, cULus, CSA

Accessories:



[Hose-proof protection hood FC 4000 000](#)



[Hose-proof protection hood FC 4000 000 FDA](#)



[Adjustable Thermostat NO](#)

Technical Data


Operating Temperature Range:	-10°C - 55°C
Air flow unimpeded:	26 m³/h
Static pressure:	57 Pa
Dimensions A x B x C (D+E):	106.5 x 106.5 x 79.5 mm
Weight:	0.54 kg
Cut out dimensions:	92.5 x 92.5 (+0.5) mm
Voltage / Frequency:	120 V ~ 60 Hz
Rated current:	0.13 A
Power consumption:	10 W
Degree of separation:	85% - DIN 24185
Wall thickness:	1 - 2 mm
Filter class:	G3 according to EN 779
Installation:	Elastic clips
Noise level:	42 dB(A)

Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).
 > [Overview Product Group Filter fans & exhaust filters](#)

Air flow:


Q = Air flow [m³/h]

P = Static pressure [Pa]



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

In RAL 9005	4023A3003
With TYPE 3R protection part no.	4023A3030
Taric code	84145915
GTIN (EAN)	5350604100190