

Filter Fan



Description

Order Number:	4610D2000
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54, Type 12, 3R
Optional:	Different housing colors available on request
Approvals:	CE, cURus, cULus, CSA

Accessories:



[Hose-proof protection hood FC 4000 300](#)



[Hose-proof protection hood FC 4000 300 FDA](#)



[Adjustable Thermostat NO](#)


Technical Data

Operating Temperature Range:	-10°C - 55°C
Air flow unimpeded:	225 m³/h
Static pressure:	99 Pa
Dimensions A x B x C (D+E):	250 x 250 x 124.2 mm
Weight:	1.4 kg
Cut out dimensions:	223 x 223 (+1.5) mm
Voltage / Frequency:	24 V DC
Rated current:	0.71 A
Power consumption:	17 W
Wall thickness:	1.5 - 2.5 mm
Filter class:	G3 according to EN 779
Installation:	Elastic clips
Noise level:	58 dB(A)

Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).
 > [Overview Product Group Filter fans & exhaust filters](#)


Air flow:

Q = Air flow [m³/h]
P = Static pressure [Pa]



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

IN RAL 9005	4610D2003
Taric code	84145915
GTIN (EAN)	5350604100442