

Control Cabinet Air Conditioner



Description

Order Number:	4305002
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress Protection:	IP 54 / TYPE 12
Approvals:	CE, cURus, cULus

Technical Data

Cooling capacity L35L35:	550 W @ 50 Hz 620 W @ 60 Hz
Cooling capacity L35L50:	410 W @ 50 Hz 440 W @ 60 Hz
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	127 g / 4.5 oz
High / low Pressure:	23.3 / 5.3 bar 338 / 77 psig
Operating Temperature Range:	10°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 435 / 550 m³/h Cabinet air circuit: 200 / 250 m³/h
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	650 x 315 x 260 mm
Weight:	27.7 Kg
Cut out dimensions:	635 x 275 mm
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current L35L35:	2.1 A
Starting current:	9.8 A
Max. current:	2.5 A
Nominal power L35L35:	370 W @ 50 Hz 400 W @ 60 Hz
Max. power:	510 W
Fuse:	6 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).
 > [Overview Product Group Cooling Units - COMPACT](#)

