

## Cooling unit NEMA / type 4X



### Description

|                            |                                               |
|----------------------------|-----------------------------------------------|
| <b>Order Number:</b>       | 57040062                                      |
| <b>Colour:</b>             | -                                             |
| <b>Housing Material:</b>   | Stainless steel AISI 304 (V2A)                |
| <b>Ingress Protection:</b> | IP 56 / Type 12, 3, 3R, 4, 4X                 |
| <b>SK notes:</b>           | With cabinet heater<br>With metal mash filter |
| <b>Optional:</b>           | -                                             |
| <b>Approvals:</b>          | CE, cURus, cULus                              |
| <b>UL File Number:</b>     | cURus (SA32278), cULus (E498756)              |

## Technical Data

|                                              |                                                                          |
|----------------------------------------------|--------------------------------------------------------------------------|
| <b>Cooling capacity L35L35:</b>              | 290 W @ 50 Hz<br>300 W @ 60 Hz                                           |
| <b>Cooling capacity L35L50:</b>              | 250 W @ 50 Hz<br>250 W @ 60 Hz                                           |
| <b>Compressor type:</b>                      | Rotary piston compressor                                                 |
| <b>Refrigerant / GWP:</b>                    | R 134a / 1430                                                            |
| <b>Refrigerant charge:</b>                   | 115 g / 4.05 oz                                                          |
| <b>High / low Pressure:</b>                  | 29.3 / 6.1 bar<br>425 / 88 psig                                          |
| <b>Operating Temperature Range:</b>          | -40°C - 55°C                                                             |
| <b>Air flow volume (system / unimpeded):</b> | Ambient air circuit: 85 / 300 m³/h<br>Cabinet air circuit: 85 / 136 m³/h |
| <b>Mounting:</b>                             | Wall mounted                                                             |
| <b>Dimensions A x B x C (D+E):</b>           | 480 x 250 x 190 mm                                                       |
| <b>Weight:</b>                               | 15.2 kg                                                                  |
| <b>Cut out dimensions:</b>                   | 204 x 250 mm                                                             |
| <b>Voltage / Frequency:</b>                  | 230 V ~ 50/60 Hz                                                         |
| <b>UL Voltage / Frequency:</b>               | 230 V ~ 60 Hz                                                            |
| <b>Current L35L35:</b>                       | 1.3 A                                                                    |
| <b>Starting current:</b>                     | 5 A                                                                      |
| <b>Max. current:</b>                         | 1.5 A                                                                    |
| <b>Nominal power L35L35:</b>                 | 270 W                                                                    |
| <b>Max. power:</b>                           | 325 W                                                                    |
| <b>Fuse:</b>                                 | 2.5 A (T)                                                                |
| <b>Short-circuit current rating:</b>         | 5 kA                                                                     |
| <b>Connection:</b>                           | Connection terminal block                                                |

Please click on the graphics to download.  
 More CAD drawings can be found under [Product Download](#).  
 > [Overview Product Group Cooling Units Outdoor / Type 4X](#)

