

Control Cabinet Air Conditioner



Description

Order Number:	4340002
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress Protection:	IP 54 / TYPE 12
Approvals:	CE, cURus, cULus


Technical Data

Cooling capacity L35L35:	4 kW @ 50 Hz 4 kW @ 60 Hz
Cooling capacity L35L50:	3.18 kW @ 50 Hz 3.36 kW @ 60 Hz
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	855 g / 30.15 oz
High / low Pressure:	28 / 6 bar 406 / 88 psig
Operating Temperature Range:	10°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 1050 / 1500 m³/h Cabinet air circuit: 860 / 1200 m³/h
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	1,230 x 500 x 340 mm
Weight:	69 kg
Cut out dimensions:	1,130 x 430 mm
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current L35L35:	8.9 A @ 50 Hz 10.2 A @ 60 Hz
Starting current:	29.6 A
Max. current:	14.2 A
Nominal power L35L35:	1.88 kW @ 50 Hz 2.31 kW @ 60 Hz
Max. power:	2.40 kW @ 50 Hz 3.72 kW @ 60 Hz
Fuse:	20 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).


> [Overview Product Group Cooling Units - COMPACT](#)

Performance graph:




[click image to enlarge](#)

Air flow:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)