

Outdoor cooling unit



Description


Order Number:	57410062
Colour:	-
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress Protection:	IP 56 / Type 12, 3, 3R, 4, 4X
Optional:	-
Approvals:	CE, cURus, cULus
UL File Number:	cURus (SA32278), cULus (E498756)

Technical Data

Cooling capacity L35L35:	4 kW @ 50 Hz 4 kW @ 60 Hz
Cooling capacity L35L50:	3.18 kW @ 50 Hz 3.36 kW @ 60 Hz
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	975 g / 34.4 oz
High / low Pressure:	27.7 / 6 bar 406 / 88 psig
Operating Temperature Range:	-40°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 990 / 1500 m³/h Cabinet air circuit: 950 / 1200 m³/h
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	1,550 x 457 x 355 mm
Weight:	82 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current L35L35:	8.9 A @ 50 Hz 10.2 A @ 60 Hz
Starting current:	50 A
Max. current:	13.7 A
Nominal power L35L35:	2.0 kW @ 50 Hz 2.5 kW @ 60 Hz
Max. power:	2,40 kW @ 50 Hz 3,27 kW @ 60 Hz
Fuse:	20 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block


Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).
 > [Overview Product Group Cooling Units Outdoor / Type 4X](#)

Performance graph:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)