

Thermoelectric cooling unit



Description


Order Number:	31523054
Housing Material:	Stainless steel AISI 316 (V4A)
Ingress Protection:	IP 66 / UL Type 12, 4, 4X
Included:	Mounting frame
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus

Technical Data

Cooling capacity L35L35:	150 W
Operating Temperature Range:	-20°C - 70°C
UL temperature range:	-20°C - 65°C
Air flow volume (system / unimpeded):	Ambient air circuit: 120 / 260 m³/h Cabinet air circuit: 60 / 170 m³/h
Mounting:	Wall mounted (with frame)
Dimensions A x B x C (D+E):	500 x 188 x 168 mm
Weight:	12.7 kg
Cut out dimensions:	469 x 155 mm
Voltage / Frequency:	24 V DC
Current L35L35:	6.3 A
Starting current:	11 A
Max. current:	7.9 A
Nominal power L35L35:	170 W
Max. power:	188 W
Fuse:	10 A (T)
Connection:	Connection terminal block


Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).
 > [Overview Product Group Cooling Units - PELTIER](#)

Performance graph:




click image to enlarge

Air flow:



click image to enlarge

Cut Out Dimension:



click image to enlarge