

Thermoelectric cooling unit



Description

Order Number:	3035305
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress Protection:	IP 66 / UL Type 12, 4, 4X
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE
Accessories:	




[Condensate Kit 3030 / 3050](#)

Technical Data

Cooling capacity L35L35:	30 W
Operating Temperature Range:	-20°C - 70°C
UL temperature range:	-20°C - 65°C
Air flow volume (system / unimpeded):	Ambient air circuit: 39 / 75 m³/h Cabinet air circuit: 20 / 62 m³/h
Mounting:	Wall mounted (with frame)
Dimensions A x B x C (D+E):	212 x 158 x 132 mm
Weight:	2.6 kg
Cut out dimensions:	180 x 128 mm
Voltage / Frequency:	24 V DC
Current L35L35:	2 A
Starting current:	4 A
Max. current:	2.2 A
Nominal power L35L35:	44 W
Max. power:	52 W
Fuse:	5 A (T)
Connection:	Connection terminal block


Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).
 > [Overview Product Group Cooling Units - PELTIER](#)

Performance graph:




[click image to enlarge](#)

Air flow:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

Stainless steel AISI 316 (V4A) housing part no.	30353054
Box dimension	244 x 187 x 174 mm
Gross weight	2.5 kg
Taric code	84158300