



SEMiX® 13

Trench IGBT Modules

SEMiX101GD066HDs

Features


- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- UL recognised file no. E63532

Typical Applications*

- Matrix Converter
- Resonant Inverter
- Current Source Inverter

Remarks

- Case temperature limited to $T_C=125^\circ\text{C}$ max.
- Product reliability results are valid for $T_J=150^\circ\text{C}$
- For short circuit: Soft R_{Goff} recommended
- Take care of over-voltage caused by stray inductance



GD

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
IGBT				
V _{CES}			600	V
I _C	T _j = 175 °C	T _c = 25 °C	139	A
		T _c = 80 °C	105	A
I _{Cnom}			100	A
I _{CRM}	I _{CRM} = 2xI _{Cnom}		200	A
V _{GES}			-20 ... 20	V
t _{psc}	V _{CC} = 360 V V _{GE} ≤ 15 V V _{CES} ≤ 600 V	T _j = 150 °C	6	μs
T _j			-40 ... 175	°C
Inverse diode				
I _F	T _j = 175 °C	T _c = 25 °C	151	A
		T _c = 80 °C	111	A
I _{Fnom}			100	A
I _{FRM}	I _{FRM} = 2xI _{Fnom}		200	A
I _{FSM}	t _p = 10 ms, sin 180°, T _j = 25 °C		500	A
T _j			-40 ... 175	°C
Module				
I _{t(RMS)}			600	A
T _{stg}			-40 ... 125	°C
V _{isol}	AC sinus 50Hz, t = 1 min		4000	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT						
V _{CE(sat)}	I _C = 100 A	T _j = 25 °C		1.45	1.85	V
	V _{GE} = 15 V chipelevel	T _j = 150 °C		1.7	2.1	V
V _{CE0}		T _j = 25 °C		0.9	1	V
		T _j = 150 °C		0.85	0.9	V
r _{CE}	V _{GE} = 15 V	T _j = 25 °C		5.5	8.5	mΩ
		T _j = 150 °C		8.5	12.0	mΩ
V _{GE(th)}	V _{GE} =V _{CE} , I _C = 1.6 mA		5	5.8	6.5	V
I _{CES}	V _{GE} = 0 V	T _j = 25 °C		0.15	0.45	mA
	V _{CE} = 600 V	T _j = 150 °C				mA
C _{ies}	V _{CE} = 25 V V _{GE} = 0 V	f = 1 MHz		6.2		nF
C _{oes}		f = 1 MHz		0.38		nF
C _{res}		f = 1 MHz		0.18		nF
Q _G	V _{GE} = - 8 V...+ 15 V			800		nC
R _{Gint}	T _j = 25 °C			2.00		Ω
t _{d(on)}	V _{CC} = 300 V	T _j = 150 °C		140		ns
t _r	I _C = 100 A	T _j = 150 °C		35		ns
E _{on}	R _{G on} = 6.2 Ω R _{G off} = 6.2 Ω	T _j = 150 °C		3		mJ
t _{d(off)}		T _j = 150 °C		440		ns
t _f		T _j = 150 °C		55		ns
E _{off}		T _j = 150 °C		4		mJ
R _{th(j-c)}	per IGBT				0.41	K/W



SEMiX® 13

Trench IGBT Modules

SEMiX101GD066HDs

Features

- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- UL recognised file no. E63532


Typical Applications*

- Matrix Converter
- Resonant Inverter
- Current Source Inverter

Remarks

- Case temperature limited to $T_C=125^\circ\text{C}$ max.
- Product reliability results are valid for $T_J=150^\circ\text{C}$
- For short circuit: Soft R_{Goff} recommended
- Take care of over-voltage caused by stray inductance

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Inverse diode						
V _F = V _{EC}	I _F = 100 A	T _j = 25 °C		1.4	1.60	V
	V _{GE} = 0 V chip	T _j = 150 °C		1.4	1.6	V
V _{F0}		T _j = 25 °C	0.9	1	1.1	V
		T _j = 150 °C	0.75	0.85	0.95	V
r _F		T _j = 25 °C	3.0	4.0	5.0	mΩ
		T _j = 150 °C	4.5	5.5	6.5	mΩ
I _{RRM}	I _F = 100 A	T _j = 150 °C		130		A
Q _{rr}	di/dt _{off} = 3200 A/μs	T _j = 150 °C		18		μC
E _{rr}	V _{GE} = -8 V V _{CC} = 300 V	T _j = 150 °C		4.5		mJ
R _{th(j-c)}	per diode				0.51	K/W
Module						
L _{CE}				20		nH
R _{CC'+EE'}	res., terminal-chip	T _C = 25 °C		0.7		mΩ
		T _C = 125 °C		1		mΩ
R _{th(c-s)}	per module			0.04		K/W
M _s	to heat sink (M5)		3		5	Nm
M _t		to terminals (M6)	2.5		5	Nm
						Nm
w					350	g
Temperatur Sensor						
R ₁₀₀	T _c =100°C (R ₂₅ =5 kΩ)			493 ± 5%		Ω
B _{100/125}	R _(T) =R ₁₀₀ exp[B _{100/125} (1/T-1/T ₁₀₀)]; T[K];			3550 ±2%		K



GD




Fig. 1: Typ. output characteristic, inclusive $R_{CC} + EE'$




Fig. 2: Rated current vs. temperature $I_C = f(T_C)$




Fig. 3: Typ. turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic










Fig. 6: Typ. gate charge characteristic





* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.