



Twin 6-pack

SKiiP 24ACC12T4V1

Features*


- Trench 4 IGBTs
- Robust and soft switching freewheeling diodes in CAL technology
- Highly reliable spring contacts for electrical connections
- UL recognized: File no. E63532

Typical Applications

- 4Q inverters

Remarks

- Max. case temperature limited to $T_c=125^\circ\text{C}$
- Product reliability results valid for $T_j \leq 150^\circ\text{C}$ (recommended $T_{j,\text{op}}=-40\ldots+150^\circ\text{C}$)
- Terminal distances sufficient for basic insulation in 3-phase 480VAC TN systems
- DC-link voltage $V_{\text{DC}} \leq 800\text{V}$
- Temperature sensor: no basic insulation to main circuit, signal processing with reference to $-DC$ potential
- Please refer to MiniSKiiP "Technical Explanations" and "Mounting Instructions" for further information
- Inverter - IGBT=T1-T12
- Inverse - Diode=D1-D12



Absolute Maximum Ratings		Values	Unit	
Symbol	Conditions			
IGBT 1 - 6				
V_{CES}			V	
I_c	$\lambda_{\text{paste}}=0.8 \text{ W}/(\text{mK})$ $T_j = 175^\circ\text{C}$	$T_s = 25^\circ\text{C}$	A	
I_c	$\lambda_{\text{paste}}=2.5 \text{ W}/(\text{mK})$	$T_s = 70^\circ\text{C}$	A	
I_{Cnom}		$T_s = 70^\circ\text{C}$	A	
I_{CRM}			A	
V_{GES}			V	
t_{psc}	$V_{\text{GE}} \leq V$ $V_{\text{CES}} \leq V$	n.c.	μs	
T_j			$^\circ\text{C}$	
IGBT 7 - 12				
V_{CES}	$T_j = 25^\circ\text{C}$	1200	V	
I_c	$\lambda_{\text{paste}}=0.8 \text{ W}/(\text{mK})$ $T_j = 175^\circ\text{C}$	38	A	
I_c	$\lambda_{\text{paste}}=2.5 \text{ W}/(\text{mK})$ $T_j = 175^\circ\text{C}$	31	A	
I_{Cnom}		42	A	
I_{CRM}		35	A	
V_{GES}		-20 ... 20	V	
t_{psc}	$V_{\text{CC}} = 800\text{V}$ $V_{\text{GE}} \leq 15\text{V}$ $V_{\text{CES}} \leq 1200\text{V}$	$T_j = 150^\circ\text{C}$	10	μs
T_j		-40 ... 175	$^\circ\text{C}$	
Diode 1 - 6				
V_{RRM}			V	
I_F	$\lambda_{\text{paste}}=0.8 \text{ W}/(\text{mK})$ $T_s = 25^\circ\text{C}$	25	A	
I_F	$\lambda_{\text{paste}}=2.5 \text{ W}/(\text{mK})$ $T_s = 70^\circ\text{C}$	31	A	
I_{FRM}		42	A	
I_{FSM}	, ,	35	A	
T_j		175	$^\circ\text{C}$	
Diode 7 - 12				
V_{RRM}	$T_j = 25^\circ\text{C}$	1200	V	
I_F	$\lambda_{\text{paste}}=0.8 \text{ W}/(\text{mK})$ $T_j = 175^\circ\text{C}$	31	A	
I_F	$\lambda_{\text{paste}}=2.5 \text{ W}/(\text{mK})$ $T_j = 175^\circ\text{C}$	25	A	
I_{FRM}		34	A	
I_{FSM}		27	A	
T_j		50	A	
I_{FSM}	$10 \text{ ms, sin } 180^\circ, T_j = 150^\circ\text{C}$	100	A	
T_j		-40 ... 175	$^\circ\text{C}$	
Module				
$I_{\text{t(RMS)}}$	20 A per spring	40	A	
T_{stg}	module without TIM	-40 ... 125	$^\circ\text{C}$	
V_{isol}	AC sinus 50 Hz, 1 min	2500	V	



Twin 6-pack

SKiiP 24ACC12T4V1

Features*


- Trench 4 IGBTs
- Robust and soft switching freewheeling diodes in CAL technology
- Highly reliable spring contacts for electrical connections
- UL recognized: File no. E63532

Typical Applications

- 4Q inverters

Remarks

- Max. case temperature limited to $T_C=125^\circ\text{C}$
- Product reliability results valid for $T_j \leq 150^\circ\text{C}$ (recommended $T_{j,\text{op}}=-40\ldots+150^\circ\text{C}$)
- Terminal distances sufficient for basic insulation in 3-phase 480VAC TN systems
- DC-link voltage $V_{DC} \leq 800\text{V}$
- Temperature sensor: no basic insulation to main circuit, signal processing with reference to $-DC$ potential
- Please refer to MiniSKiiP "Technical Explanations" and "Mounting Instructions" for further information
- Inverter - IGBT=T1-T12
- Inverse - Diode=D1-D12



Characteristics		Conditions	min.	typ.	max.	Unit
Symbol						
IGBT 1 - 6						
$V_{CE(\text{sat})}$						V
						V
V_{CE0}	chiplevel					V
						V
r_{CE}						$\text{m}\Omega$
						$\text{m}\Omega$
$V_{GE(\text{th})}$,					V
I_{CES}					0.3	mA
						mA
C_{ies}						nF
C_{oes}						nF
C_{res}						nF
Q_G						nC
R_{Gint}				0		Ω
$t_{d(on)}$						ns
t_r						ns
E_{on}						mJ
$t_{d(off)}$						ns
t_f						ns
E_{off}	$V_{GE} = +15/-15\text{ V}$					mJ
$R_{th(j-s)}$	per IGBT, $\lambda_{\text{paste}}=0.8\text{ W}/(\text{mK})$					K/W
$R_{th(j-s)}$	per IGBT, $\lambda_{\text{paste}}=2.5\text{ W}/(\text{mK})$					K/W
IGBT 7 - 12						
$V_{CE(\text{sat})}$	$I_C = 25\text{ A}$ $V_{GE} = 15\text{ V}$ chiplevel	$T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$		1.85	2.10	V
				2.25	2.45	V
V_{CE0}	chiplevel	$T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$		0.80	0.90	V
				0.70	0.80	V
r_{CE}	$V_{GE} = 15\text{ V}$ chiplevel	$T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$		42	48	$\text{m}\Omega$
				62	66	$\text{m}\Omega$
$V_{GE(\text{th})}$	$V_{GE} = V_{CE}\text{ V}$, $I_C = 1\text{ mA}$		5.3	5.8	6.3	V
I_{CES}	$V_{GE} = 0\text{ V}$ $V_{CE} = 1200\text{ V}$	$T_j = 25^\circ\text{C}$			1	mA
					-	mA
C_{ies}		$f = 1\text{ MHz}$			1.45	nF
C_{oes}	$V_{CE} = 25\text{ V}$ $V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$			0.12	nF
C_{res}		$f = 1\text{ MHz}$			0.05	nF
Q_G	$V_{GE} = -8\text{ V} \ldots +15\text{ V}$				142	nC
R_{Gint}	$T_j = 25^\circ\text{C}$				0	Ω
$t_{d(on)}$	$V_{CC} = 600\text{ V}$	$T_j = 150^\circ\text{C}$		39		ns
t_r	$I_C = 25\text{ A}$	$T_j = 150^\circ\text{C}$		32		ns
E_{on}	$R_{G\text{ on}} = 27\text{ }\Omega$ $R_{G\text{ off}} = 27\text{ }\Omega$	$T_j = 150^\circ\text{C}$		3.2		mJ
$t_{d(off)}$	$di/dt_{\text{on}} = 780\text{ A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$		333		ns
t_f	$di/dt_{\text{off}} = 360\text{ A}/\mu\text{s}$ $dv/dt = 3400\text{ V}/\mu\text{s}$	$T_j = 150^\circ\text{C}$		91		ns
E_{off}	$V_{GE} = +15/-15\text{ V}$ $L_s = 21\text{ nH}$	$T_j = 150^\circ\text{C}$		3		mJ
$R_{th(j-s)}$	per IGBT, $\lambda_{\text{paste}}=0.8\text{ W}/(\text{mK})$				1.13	K/W
$R_{th(j-s)}$	per IGBT, $\lambda_{\text{paste}}=2.5\text{ W}/(\text{mK})$				0.94	K/W

SKiiP 24ACC12T4V1



Twin 6-pack

SKiiP 24ACC12T4V1

Features*

- Trench 4 IGBTs
- Robust and soft switching freewheeling diodes in CAL technology
- Highly reliable spring contacts for electrical connections
- UL recognized: File no. E63532


Typical Applications







- 4Q inverters

Remarks

- Max. case temperature limited to $T_C=125^\circ\text{C}$
- Product reliability results valid for $T_j \leq 150^\circ\text{C}$ (recommended $T_{j,\text{op}}=-40\ldots+150^\circ\text{C}$)
- Terminal distances sufficient for basic insulation in 3-phase 480VAC TN systems
- DC-link voltage $V_{DC} \leq 800\text{V}$
- Temperature sensor: no basic insulation to main circuit, signal processing with reference to $-DC$ potential
- Please refer to MiniSKiiP "Technical Explanations" and "Mounting Instructions" for further information
- Inverter - IGBT=T1-T12
- Inverse - Diode=D1-D12

Characteristics		Symbol	Conditions	min.	typ.	max.	Unit						
Diode 1 - 6													
$V_F = V_{EC}$	$I_F = 25\text{ A}$ $V_{GE} = 0\text{ V}$		$T_j = 25^\circ\text{C}$				V						
V_{FO}	chiplevel		$T_j = 25^\circ\text{C}$				V						
r_F	chiplevel		$T_j = 25^\circ\text{C}$	0.00	0.00		$\text{m}\Omega$						
				0.00	0.00		$\text{m}\Omega$						
I_{RRM}			$T_j = 150^\circ\text{C}$		t.b.d.		A						
Q_{rr}	$V_{GE} = -15\text{ V}$		$T_j = 150^\circ\text{C}$		t.b.d.		μC						
E_{rr}			$T_j = 150^\circ\text{C}$		t.b.d.		mJ						
$R_{th(j-s)}$	per Diode, $\lambda_{\text{paste}}=0.8\text{ W}/(\text{mK})$						K/W						
$R_{th(j-s)}$	per Diode, $\lambda_{\text{paste}}=2.5\text{ W}/(\text{mK})$						K/W						
Diode 7 - 12													
$V_F = V_{EC}$	$I_F = 25\text{ A}$ $V_{GE} = 0\text{ V}$ chiplevel		$T_j = 25^\circ\text{C}$	2.41	2.74		V						
			$T_j = 150^\circ\text{C}$	2.45	2.79		V						
V_{FO}	chiplevel		$T_j = 25^\circ\text{C}$	1.30	1.50		V						
			$T_j = 150^\circ\text{C}$	0.90	1.10		V						
r_F	chiplevel		$T_j = 25^\circ\text{C}$	44	50		$\text{m}\Omega$						
			$T_j = 150^\circ\text{C}$	62	68		$\text{m}\Omega$						
I_{RRM}	$I_F = 25\text{ A}$		$T_j = 150^\circ\text{C}$	23			A						
Q_{rr}	$di/dt_{\text{off}} = 732\text{ A}/\mu\text{s}$		$T_j = 150^\circ\text{C}$	3.8			μC						
E_{rr}	$V_{GE} = -15\text{ V}$ $V_{CC} = 600\text{ V}$		$T_j = 150^\circ\text{C}$	1.4			mJ						
$R_{th(j-s)}$	per Diode, $\lambda_{\text{paste}}=0.8\text{ W}/(\text{mK})$			1.6			K/W						
$R_{th(j-s)}$	per Diode, $\lambda_{\text{paste}}=2.5\text{ W}/(\text{mK})$			1.37			K/W						
Module													
L_{CE}				-			nH						
M_s	to heat sink			2	2.5		Nm						
W				55			g						
Temperature Sensor													
R_{100}	$T_r=100^\circ\text{C}$ ($R_{25}=1000\Omega$)			$1670 \pm 3\%$			Ω						
$R_{(T)}$	$R_{(T)}=1000\Omega[1+A(T-25^\circ\text{C})+B(T-25^\circ\text{C})^2]$, $A = 7.635 \cdot 10^{-3} \cdot \text{C}^{-1}$ $B = 1.731 \cdot 10^{-5} \cdot \text{C}^{-2}$												








Fig. 7: Typ. switching times vs. I_C




Fig. 8: Typ. switching times vs. gate resistor R_G




Fig. 9: Typ. transient thermal impedance




Fig. 10: Typ. CAL diode forward characteristic




Fig. 11: Typ. CAL diode peak reverse recovery current






Fig. 12: Typ. CAL diode recovery charge

Pin out											
Pin	X	Y	Function	Pin	X	Y	Function	Pin	X	Y	Function
1	24,38	-21,80	DC+	23	8,38	5,80		45	-12,23	-5,80	g2
2	24,38	-18,60		24	8,38	12,20	g8	46	-12,23	0,70	g3
3	24,38	-15,40	g11	25	8,38	15,40		47	-12,23	3,90	E3
4	24,38	-12,20	E11	26	8,38	18,60		48	-12,23	7,10	L2
5	24,38	-9,00	W	27	8,38	21,80		49	-12,23	10,30	L2
6	24,38	-5,80	W	28	2,46	-21,80	DC+	50	-12,23	15,40	
7	24,38	-2,60		29	2,46	-18,60		51	-12,23	18,60	
8	24,38	12,20	g12	30	2,46	-15,40	g7	52	-12,23	21,80	g6
9	24,38	15,40		31	2,46	-12,20	E7	53	-24,38	-18,60	g1
10	24,38	18,60	T+	32	2,46	-9,00	U	54	-24,38	-18,60	
11	24,38	21,80	T-	33	2,46	-5,80	U	55	-24,38	-15,40	
12	16,58	12,20	g10	34	0,03	5,80		56	-24,38	-12,20	rect+
13	16,58	15,40	DC-/E	35	0,03	9,00	rect-/E	57	-24,38	-9,00	rect+
14	16,58	18,60	DC-	36	0,03	12,20	rect-	58	-24,38	-5,80	rect+
15	16,58	21,80	DC-	37	0,03	15,40	rect-	59	-24,38	-2,60	
16	13,42	-21,80	DC+	38	0,03	18,60		60	-24,38	0,70	
17	13,42	-18,60		39	0,03	21,80	g4	61	-24,38	3,90	
18	13,42	-15,40	g9	40	-8,51	-21,80	E1	62	-24,38	7,10	g5
19	13,42	-12,20	E9	41	-8,51	-18,60	L1	63	-24,38	15,40	E5
20	13,42	-9,00	V	42	-8,51	-15,40	L1	64	-24,38	18,60	L3
21	13,42	-5,80	V	43	-8,51	-12,20		65	-24,38	21,80	L3
22	8,38	2,60		44	-12,23	-9,00					

all values in mm



Pinout and Dimensions



Pinout

This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

*IMPORTANT INFORMATION AND WARNINGS

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.