

Empty enclosure

GTi 5-t



GTi 5-t

Empty enclosure

CUSTOMIZABLE

Productnumber: 01000501

Dimensions: 440 x 640 x 179 mm

Empty Enclosure - Industrial Quality -, 4 x housing connectors (GGV)

with transparent cover



Technical Data

electrical characteristics

Rated insulation voltage AC:	690 V
Rated insulation voltage DC:	1000 V
Protection class:	II
Type of protection:	IP65
Protection type UL:	3R

Colours

Base unit colour:	grey
-------------------	------

Dimensions

Width:	440 mm
Length:	640 mm
Height:	179 mm

Dimensions

Inner height:	157 mm
---------------	--------

Material characteristics

suitable for exterior use:	yes
Industry quality:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability according to EN 60695-2-11:	960 °C

mechanical properties

Type of fastening:	Surface mounted
Impact strength:	IK08
Cover screw torque:	2.5 Nm
Stackable:	yes

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

Accessories

[07335001 - GFW 30 - Weather protection cover](#)

[07345001 - GFW 40 - Weather protection cover](#)

[07251501 - GFS 15-m - Flange set](#)