

Socket enclosure

STG 024 BE/FR

STG 024 BE/FR

Socket enclosure

CUSTOMIZABLE

Productnumber: 73222405

Dimensions: 250 x 200 x 122 mm

Socket enclosure, with protection class IP44, with integrated, pre-wired sockets, high mechanical resilience, non-sensitive to temperature, combinable, halogen-free

equipped with: 4 x Protective contact socket, French/Belgian standard (on front), 230V 2 x CEE plug socket outlet (on front) 16A, 400V



Technical Data

Built-in devices

Protective contact socket, French/Belgian standard (on front), 230V :	4
CEE plug socket outlet (on front) 16A, 400V:	2

electrical characteristics

Rated insulation voltage AC:	400 V
Protection class:	II
Type of protection:	IP44
Number of rows:	0

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Width:	250 mm
Length:	200 mm
Height:	122 mm

Material characteristics

suitable for exterior use:	yes
Industry quality:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability according to EN 60695-2-11:	850 °C

mechanical properties

Type of fastening:	Wall mounting
Impact strength:	IK08

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate, glass-fibre reinforced
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced