


Small-scale distributors

AK 42 UL



AK 42 UL

Small-scale distributors

CUSTOMIZABLE

Productnumber: 73344252

Dimensions: 315 x 600 x 155 mm

Small-scale distributors, with protection class IP65, Protection type UL 3R, 12/12K, with integrated ventilation elements for reducing the formation of condensation, Rated operational voltage: 400V AC, Rated insulation voltage: 1000V AC, 1500V DC, certified according to VDE (DIN EN 60670-1/-24 (VDE 0606-1/-24)), DLG (Ammonia resistance), UL-EU (EN 62208), UL-EU (EN 61439-1/-2), UL-EU (EN 61439-1/-3), UL (UL 50 & CSA 22.2 No. 94.1-07, UL 50E & CSA C22.2 No. 94.2-07), metric knockouts on top and bottom for universal cable insertions with cable glands and/or double membrane seals, 10 open entries on top for UL-compliant line insertion points

3-row, 42 available modules, without PE/N terminal



Reliable - The high protection class (IP65) and the robust, halogen-free design ensure reliable operation even in a tough industrial environment.

Technical Data

electrical characteristics

Rated operating voltage AC:	400 V
Rated insulation voltage AC:	1000 V
Rated insulation voltage DC:	1500 V
Protection class:	II
Type of protection:	IP65
vented:	yes
Number of modules per row:	42

electrical characteristics

with N terminal:	no
with PE terminal:	no
Protection type UL:	3R, 12/12K

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Width:	315 mm
Length:	600 mm
Height:	155 mm
Inner length:	580 mm
Inner width:	295 mm
Inner height:	106 mm

Material characteristics

suitable for exterior use:	yes
Industry quality:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability according to EN 60695-2-11:	850 °C

mechanical properties

Type of fastening:	Surface mounting
Impact strength:	IK08
Sealable:	yes
Cover screw torque:	1.2 Nm
Flange variant:	no
Stackable:	yes

Ambient conditions

max. relative humidity 25°C:	90 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C

Material

Base unit material:	Polycarbonate, glass-fibre reinforced
---------------------	---------------------------------------

Material

Cover material:	Polycarbonate
Entry material:	not relevant
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced
Hinged window material:	Polycarbonate

Certificates

Test mark:	VDE (DIN EN 60670-1/-24 (VDE 0606-1/-24))
Test mark:	DLG (Ammonia resistance)
Test mark:	UL-EU (EN 62208)
Test mark:	UL-EU (EN 61439-1/-2)
Test mark:	UL-EU (EN 61439-1/-3)
Test mark:	UL (UL 50 & CSA 22.2 No. 94.1-07, UL 50E & CSA C22.2 No. 94.2-07)

Accessories

[79901252 - AK AS UL - Masking off strips](#)

[70610201 - AK SGA-1 - Lock fittings](#)

[70690201 - AK SGA-2 - Lock fittings](#)

[73383001 - AK3 KS M50 - Combination cable gland](#)

[73383301 - AK3 ABL-ES - External fixing lugs](#)