


Small-scale distributors

AK-F 28



AK-F 28

Small-scale distributors

CUSTOMIZABLE

Productnumber: 73352801

Dimensions: 315 x 450 x 155 mm

Small-scale distributors, with protection class IP65, 2 Rows, 28 available modules, Flange type, with integrated ventilation elements for reducing the formation of condensation, Rated operational voltage: 400V AC, Rated insulation voltage: 1000V AC, 1500V DC, certified according to VDE (DIN EN 60670-1/-24 (VDE 0606-1/-24)), DLG (Ammonia resistance), UL-EU (EN 62208), UL-EU (EN 61439-1/-2), UL-EU (EN 61439-1/-3), UL-EU (EN 61439-1 & EN IEC 61439-7), open top/bottom sides for the use with various flanges or for the combination of several AK-F distributors via combination flange

with screwless PE/N terminal rail, with respectively 6 screwable terminal points, 2.5 - 16 mm² and 21 / 2x14 screwless terminal points, 1.5 - 4 mm²



Reliable - The high protection class (IP65) and the robust, halogen-free design ensure reliable operation even in a tough industrial environment.

Technical Data

electrical characteristics

Rated operating voltage AC:	400 V
Rated insulation voltage AC:	1000 V
Rated insulation voltage DC:	1500 V
Protection class:	II
Type of protection:	IP65
vented:	yes
Number of N-potentials:	2

electrical characteristics

Number of rows:	2
Number of modules:	28
Number of modules per row:	14

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Width:	315 mm
Length:	450 mm
Height:	155 mm
Inner length:	430 mm
Inner width:	295 mm
Inner height:	106 mm

Material characteristics

suitable for exterior use:	yes
Industry quality:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability according to EN 60695-2-11:	650 °C

mechanical properties

Type of fastening:	Surface mounting
Impact strength:	IK08
Sealable:	yes
Cover screw torque:	1.2 Nm
Flange variant:	yes
Stackable:	yes

Ambient conditions

max. relative humidity 25°C:	90 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate

Material

Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced
Hinged window material:	Polycarbonate

Certificates

Test mark:	VDE (DIN EN 60670-1/-24 (VDE 0606-1/-24))
Test mark:	DLG (Ammonia resistance)
Test mark:	UL-EU (EN 62208)
Test mark:	UL-EU (EN 61439-1/-2)
Test mark:	UL-EU (EN 61439-1/-3)
Test mark:	UL-EU (EN 61439-1 & EN IEC 61439-7)

Accessories

- [73382001 - AK3 FL00 - Flange for AK-F](#)
- [73382101 - AK3 FL01 - Flange for AK-F](#)
- [73382201 - AK3 FL02 - Flange for AK-F](#)
- [73382801 - AK3 FL13 - Flange for AK-F](#)
- [73382901 - AK3 KFL - Flange for AK-F](#)
- [19302601 - KST M25-33 - Combi connector](#)
- [70610201 - AK SGA-1 - Lock fittings](#)
- [70690201 - AK SGA-2 - Lock fittings](#)
- [73381201 - AK3 NS35-14 - Standard rail](#)
- [73381301 - AK3 NS35-275 - Standard rail](#)
- [73383001 - AK3 KS M50 - Combination cable gland](#)
- [73383101 - AK3 KBL - Cable cover with document compartment](#)
- [73383201 - AK3 TW - Partition wall](#)
- [73383301 - AK3 ABL-ES - External fixing lugs](#)
- [73383401 - AK3 STD - Mounting socket](#)
- [79080501 - KLS PE 35 - Terminal block](#)
- [79090501 - KLS N 35 - Terminal block](#)
- [79901201 - AK AS - Masking off strips](#)
- [79901301 - AK AS-v - Masking off strips](#)
- [79032101 - KLS N 1/14-SL - Plug clamps](#)
- [79032201 - KLS PE 1/14-SL - Plug clamps](#)