

Meter distribution

ZVi 9060-S



ZVi 9060-S

Meter distribution

Productnumber: 75921001

Dimensions: 600 x 900 x 210 mm

Meter distribution in multiple box-type design according to DIN EN 61439-2/-3, standard version sealable, for the surface mounting in the non-measured area, device installation surfaces according to DIN 43870-1, meter connection lines 5-pole for TN-S networks, use according to the individual release by the responsible operator, with closing and insulating seals, with included ventilation seal (IPx4) to reduce condensate water, with blanking plug, with insulating seals, with enclosed ventilation plug IP44 for reduction of condensation water

2 meter panels, each consisting of:

, Upper connection space, 150 mm, equipped with 35 mm standard rail for the support of the main line junction terminal HA 25-53 (accessories),
 Meter field, 450 mm, with transparent cover, for 1 meter with three-point mounting, with mounted meter crosspiece for three-phase meter and meter fastening screws, fastening dimensions according to DIN 43870-2,
 Lower connection space, 300 mm, standard version sealable, with 5-pole busbar system, 40 mm busbar spacing, CU12x5 mm, rated current 160A, $I_{cw} = 2.5\text{kA}$ (0.2 s), busbar terminal, for N- and PE conductors, for CU conductor 16-35 mm², with hinged window 12TE for layman operation of the automatic main circuit breakers and additional space for surge protection devices, line feed-through via cable gland (IP65, accessories) or stepped nipple M40 (IP55, included)

IP54
IP65

400V
AC



iQ

IK08



Technical Data

electrical characteristics

| | |
|------------------------------|-----------|
| Rated insulation voltage AC: | 400 V |
| Protection class: | II |
| Type of protection: | IP54/IP65 |

electrical characteristics

Protection type UL:

not specified

Dimensions

| | |
|---------|--------|
| Width: | 600 mm |
| Length: | 900 mm |
| Height: | 210 mm |

Material characteristics

| | |
|--|--------|
| suitable for exterior use: | yes |
| Industry quality: | yes |
| Halogen free: | yes |
| Flammability class according with UL94: | V2 |
| Glow-wire flammability according to EN 60695-2-11: | 850 °C |

mechanical properties

| | |
|--------------------|------------------|
| Type of fastening: | Surface mounting |
| Impact strength: | IK08 |

Ambient conditions

| | |
|------------------------------|--------|
| max. relative humidity 25°C: | 95 % |
| max. relative humidity 40°C: | 50 % |
| Min. ambient temperature: | -25 °C |
| Max. ambient temperature: | 40 °C |
| 24h ambient temperature: | 35 °C |

Material

| | |
|-----------------------|-----------------------------------|
| Base unit material: | Polycarbonate |
| Sealing material: | Polyurethane |
| Cover screw material: | Polyamide, glass-fibre reinforced |