

Meter distribution

ZVi 12060-S



ZVi 12060-S

Meter distribution

Productnumber: 75923001

Dimensions: 600 x 1200 x 210 mm

Meter distribution in multiple box-type design according to DIN EN 61439-2/-3, standard version sealable, for the surface mounting in the non-measured area, device installation surfaces according to DIN 43870-1, meter connection lines 5-pole for TN-S networks, use according to the individual release by the responsible operator, with closing and insulating seals, with included ventilation seal (IPx4) to reduce condensate water, with blanking plug, with insulating seals, with enclosed ventilation plug IP44 for reduction of condensation water

2 meter panels, each consisting of:
, Upper connection space, 300 mm, equipped with 35 mm standard rail for the support of the main line junction terminal HA25-53 (accessories), a s well as consumer space with hinged window 12TE for rail-mounted device, incl. screwless PE/N terminal rail with 3 screwable clamping units each, 2.5-16mm², 14 screwless clamping units, 1.5-4mm², Space for additional applications, 150 mm, 12 modules, equipped with 35 mm standard rail for the support of additional operation material of the operator, meter operator or metering service providers, with sealable shock protection and transparent cover,
Meter field, 450 mm, with transparent cover, for 1 meter with three-point mounting, with mounted meter crosspiece for three-phase meter and meter fastening screws, fastening dimensions according to DIN 43870-2,
Lower connection space, 300 mm, standard version sealable, with 5-pole busbar system, 40 mm busbar spacing, CU12x5 mm, rated current 160A, Icw= 2 5kA (0.2 s), busbar terminal, for N- and PE conductors, for CU conductor 16-35 mm², with hinged window 12TE for layman operation of the automatic main circuit breakers and additional space for surge protection devices, line feed-through via cable gland (IP65, accessories) or stepped nipple M40 (IP55, included)

IP54
IP65

400V
AC



iQ

IK08



Technical Data

electrical characteristics



Rated insulation voltage AC:

400 V

Protection class:

II

Type of protection:

IP54/IP65

Protection type UL:

not specified

Dimensions

Width:

600 mm

Length:

1200 mm

Height:

210 mm

Material characteristics

suitable for exterior use:

yes

Industry quality:

yes

Halogen free:

yes

Flammability class according with UL94:

V2

Glow-wire flammability according to EN 60695-2-11:

850 °C

mechanical properties

Type of fastening:

Surface mounting

Impact strength:

IK08

Ambient conditions

max. relative humidity 25 °C:

95 %

max. relative humidity 40 °C:

50 %

Min. ambient temperature:

-25 °C

Max. ambient temperature:

40 °C

24h ambient temperature:

35 °C

Material

Base unit material:

Polycarbonate

Sealing material:

Polyurethane

Cover screw material:

Polyamide, glass-fibre reinforced