

Receptacle

HW 050



HW 050

Receptacle

Productnumber: 92005001

Dimensions: 68 x 68 x 50 mm

Receptacle, with protection class IP30, Rated insulation voltage: 400V AC, certified according to VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))



Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Type of protection:	IP30
Protection type UL:	not specified

Dimensions

Width:	68 mm
Length:	68 mm
Height:	50 mm
Inner height:	48 mm

Material characteristics

Industry quality:	no
Halogen free:	no

Material characteristics

Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	850 °C

Ambient conditions

max. relative humidity 25°C:	- %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Material

Base unit material:	Plastic
Cover material:	Polypropylene

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
------------	--

Accessories

[97910501 - ES-10 - Installation screw](#)

[97910601 - ES-18 - Installation screw](#)

[97910701 - ES-25 - Installation screw](#)