

Branch socket

HW 065 H

Branch socket, with protection class IP30, Rated insulation voltage: 400V AC, certified according to VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), Halogen free



HW 065 H

Branch socket

Productnumber: 92026501

Dimensions: 68 x 68 x 65 mm

Branch socket, with protection class IP30, Rated insulation voltage: 400V AC, certified according to VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), Halogen free



Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Type of protection:	IP30
Protection type UL:	not specified

Colours

Base unit colour:	white
-------------------	-------

Dimensions

Width:	68 mm
Length:	68 mm
Height:	65 mm
Inner height:	63 mm

Material characteristics

Industry quality:	no
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	960 °C

Ambient conditions

max. relative humidity 25°C:	- %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Material

Base unit material:	Plastic
Cover material:	Polypropylene

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
------------	---

Accessories

[97910501 - ES-10 - Installation screw](#)

[97910601 - ES-18 - Installation screw](#)

[97910701 - ES-25 - Installation screw](#)