

## Conduit ferrule

# ROP 25

## ROP 25

### Conduit ferrule

Productnumber: 97052301

Dimensions: 49 x 64 x 45 mm

Conduit ferrule, with bottom section, to take various conduit diameters, Rated insulation voltage: 400V AC, Halogen free, Number of 30° insertions: 1

**adhesive fixing or nail installation, Sealing area M25, support spar compatible**



## Technical Data

### electrical characteristics

|                              |                       |
|------------------------------|-----------------------|
| Rated insulation voltage AC: | 400 V                 |
| Suitable for:                | Concrete construction |

### Dimensions

|         |       |
|---------|-------|
| Width:  | 49 mm |
| Length: | 64 mm |
| Height: | 45 mm |

### Material characteristics

|                                                    |        |
|----------------------------------------------------|--------|
| Industry quality:                                  | no     |
| Halogen free:                                      | yes    |
| Flammability class according with UL94:            | HB     |
| Glow-wire flammability according to EN 60695-2-11: | 650 °C |

## mechanical properties

|                    |                                      |
|--------------------|--------------------------------------|
| Type of fastening: | adhesive fixing or nail installation |
|--------------------|--------------------------------------|

### Ambient conditions

|                              |        |
|------------------------------|--------|
| max. relative humidity 25°C: | - %    |
| max. relative humidity 40°C: | 50 %   |
| Min. ambient temperature:    | -25 °C |
| Max. ambient temperature:    | 40 °C  |
| 24h ambient temperature:     | 35 °C  |

### Material

|                     |               |
|---------------------|---------------|
| Base unit material: | Polypropylene |
| Cover material:     | Polypropylene |

## Accessories

[97050501 - BSK 2 - blank base](#)

[97924001 - NAS-AL - IBT Accessories](#)

[97924201 - NA-AL - IBT Accessories](#)

[97924301 - NA-AL/gl - IBT Accessories](#)