

Deep box

U 71 TD-49



U 71 TD-49

Deep box

Productnumber: 97294501

Dimensions: 71 x 71 x 49 mm

Deep box, as top enclosure for all U 71 boxes when using large conduits up to M32, screw spacing 60 mm, provides additional installation space of 49mm in depth, with protection class IP00, Rated insulation voltage: 400V AC, Halogen free

attachable, membrane for perforation, Sealing area M16 - M32



Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Type of protection:	IP00
Suitable for:	Concrete construction
Protection type UL:	not specified

Colours

Cover colour:	other
---------------	-------

Dimensions

Width:	71 mm
Length:	71 mm
Height:	49 mm

Material characteristics

Industry quality:	no
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	650 °C

mechanical properties

Type of fastening:	attachable
--------------------	------------

Ambient conditions

max. relative humidity 25°C:	- %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene