

## Distributor kit UP 015



## UP 015

### Distributor kit

Productnumber: 98600001

Dimensions: 311 x 202 x 87 mm

Distributor kit, 15 distribution units, plastic frame and door, white, with spring latch, 35 mm DIN standard rail, PE/N terminals, masking off strips and labelling strips for K4 EK mounting boxes, Rated insulation voltage: 400V AC, Halogen free

### 1-row



## Technical Data

### electrical characteristics

|                              |                       |
|------------------------------|-----------------------|
| Rated insulation voltage AC: | 400 V                 |
| Suitable for:                | Concrete construction |

### Dimensions

|         |        |
|---------|--------|
| Width:  | 311 mm |
| Length: | 202 mm |
| Height: | 87 mm  |

### Material characteristics

|                                                    |        |
|----------------------------------------------------|--------|
| Industry quality:                                  | no     |
| Halogen free:                                      | yes    |
| Flammability class according with UL94:            | HB     |
| Glow-wire flammability according to EN 60695-2-11: | 650 °C |

### Ambient conditions

|                              |        |
|------------------------------|--------|
| max. relative humidity 25°C: | - %    |
| max. relative humidity 40°C: | 50 %   |
| Min. ambient temperature:    | -25 °C |
| Max. ambient temperature:    | 40 °C  |
| 24h ambient temperature:     | 35 °C  |

### Material

|                     |               |
|---------------------|---------------|
| Base unit material: | Polypropylene |
| Cover material:     | Polypropylene |