


Equipment installation box

BS 2-O



BS 2-O

Equipment installation box

Productnumber: 98790201

Dimensions: 86 x 146 x 60 mm

Equipment installation box, 2-way box for installing "British Standard" equipment; screw spacing 120.6 mm (4 3/4 inch.), with protection class IP30, Rated insulation voltage: 400V AC, Halogen free

open front section for special magnetic clip, magnet installation, membrane for perforation, Sealing area M16 - M32, support spar compatible



Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Type of protection:	IP30
Suitable for:	Concrete construction
Protection type UL:	not specified

Colours

Base unit colour:	green
Cover colour:	green

Dimensions

Width:	86 mm
Length:	146 mm
Height:	60 mm

Dimensions

Inner length:	128 mm
Inner width:	68 mm
Inner height:	37 mm

Material characteristics

Industry quality:	no
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	650 °C

mechanical properties

Type of fastening:	magnet installation
--------------------	---------------------

Ambient conditions

max. relative humidity 25°C:	- %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Material

Base unit material:	Plastic
Cover material:	Polypropylene

Accessories

[98720001 - BSM 2 - IBT Accessories](#)

[97443201 - BS 2-BSK - blank base](#)

[97412001 - BS MBR - Assembly bridge](#)

[97413001 - BS ES-30 - Installation screw](#)

[97413501 - BS ES-40 - Installation screw](#)

[97415001 - BS ES-50 - Installation screw](#)

[19599501 - LFR - Stepped drill](#)

[97410201 - BS 2 VD - sealing plate](#)

[97443101 - BS 1-BSK - blank base](#)

[97810001 - IBT LZA-OE - Hole punch](#)

[97811801 - IBT LZA-18 - Hole punch](#)

[97812301 - IBT LZA-23 - Hole punch](#)

[97915501 - WED - Expansion mandrel](#)

[98791101 - VCBS - IBT Accessories](#)