

Safety Light Curtain

Finger Protection

SG4-14IS045C1

Part Number



- Completely integrated electronics
- Quick alignment through visible red light

Technical Data

Optical Data

Range 0,25...7 m

Safety Field Height (SFH) 464 mm

Resolution 14 mm

Light Source Red Light

Wavelength 650 nm

Opening Angle $\pm 2,5^\circ$

Electrical Data

Sensor Type Emitter

Supply Voltage 24 V DC

Current Consumption ($U_b = 24$ V) 100 mA

Temperature Range -20...50 °C

Storage temperature -25...70 °C

Protection Class III

Mechanical Data

Housing Material Aluminum

Disc Material Polycarbonate

Degree of Protection IP67

Connection M12 x 1; 4-pin

Safety-relevant Data

ESPE Type (EN 61496) 4

Safety Category (EN ISO 13849-1) 4

Performance Level (EN ISO 13849-1) PL e

PFHD 4,22 x E-8 1/h

Mission Time TM (EN ISO 13849-1) 20 a

Function

Finger Protection yes

27

Control Panel No.

S5

Suitable Connection Equipment No.

2 | 2s


Suitable Mounting Technology No.

700

Suitable Receiver

SG4-14IE045C1

These safety light curtains are distinguished by their compact design. They are also equipped with numerous auxiliary functions, allowing for adaptation to the respective application in a highly individualized fashion. The adequate mounting angle BEF-SET-33 is included in the delivery.



Complementary Products

Laser Alignment Tool SZ0-LAH1


Path-Folding Mirror Z2UG002

Protection Column with Path-Folding Mirror SZ000EU125NN01

Protection Column with Protective Screen SZ000EG125NN01

Software

Ctrl. Panel



03 = Error Indicator
04 = Function Indicator
20 = Enter Button



1 = Emitter
2 = Receiver
All dimensions

