

ZAC50CN01

Part Number



- **2 digital I/O ports**
- **5 PoE-capable ports**
- **7 Industrial Ethernet ports**
- **High protection class IP67**
- **Rugged aluminium housing**

This junction allows simple connecting of up to seven Industrial Ethernet products. Five PoE-capable ports supply connected devices with the needed power. In addition, up to four PNP sensors and actuators can be connected via two digital I/O ports.

Industrial Ethernet

Technical Data

Electrical Data

Supply Voltage	18...32 V
Power consumption of device max.	0,3 A
Power consumption of system max.	2,2 A
Max. PoE Capacity	30 W
Max. Switching Current Switching Outputs	0,6 A
max. total current of the digital I/O ports	1 A
Switching Output Voltage Drop	< 2,5 V
Temperature Range	-25...60 °C
Digital I/O ports short circuit protected	yes
Digital I/O ports overload protected	yes
Digital I/O ports reverse polarity protected	yes
PoE Ports	5
Number of digital I/O ports	2
Supported PoE Standard	IEEE802.3af, IEEE802.at
Supported PoE Classes	Class 0, 1, 2, 3
Baud Rate	100 Mbit/s
Transmission Mode	Full Duplex
Auto-Crossover	yes
Auto-Negotiating	yes
Auto-Polarity	yes
Interface	EtherCAT
Protection Class	III

Mechanical Data

Material	Aluminum
Weight	1100 g
Degree of Protection	IP67
Type of Connection Power	2 x 7/8", 5-pin
Type of Connection Industrial Ethernet Ports	2 x M12; 4-pin
Type of Connection PoE Ports	5 x M12; 8-pin
Type of connection digital I/O ports	2 x M12; 4-pin
Web server	yes
EoE (Ethernet over EtherCAT)	yes
EtherCAT	●
Power Source Equipment for PoE	●
Connection Table No.	52
Suitable Connection Equipment No.	78

Complementary Products

Locking Screw for 7/8" Z0028

Locking Screw for M12 Z0027

