

**Fieldbus Gateway**  
RS-232 to Fast Ethernet

**ZAG45FN01**

Part Number



- Easy handling
- Gateway from RS-232/422/485 interfaces to Fast Ethernet

Ethernet

**Technical Data**

| Electrical Data                         |                |
|-----------------------------------------|----------------|
| Supply Voltage                          | 10...33 V DC   |
| Current Consumption Gateway (Ub = 24 V) | < 100 mA       |
| Temperature Range                       | 0...55 °C      |
| Short Circuit Protection                | yes            |
| Reverse Polarity Protection             | yes            |
| Interface                               | RS-232         |
| Baud Rate RS-232                        | < 115200 Bd    |
| Baud Rate Ethernet                      | < 100 MBd      |
| Number of Bus Clients                   | 512            |
| Protection Class                        | III            |
| Mechanical Data                         |                |
| Material                                | Plastic PA     |
| Weight                                  | 140 g          |
| Degree of Protection                    | IP20           |
| Connection Mode Supply Voltage          | Terminal Block |
| Connection RS-Side                      | Terminal Block |
| Connection Bus Side                     | RJ45           |
| DIN-Rail mounting                       | 35 mm          |
| Fast Ethernet                           | ●              |
| Connection Table No.                    | 43             |
| Suitable Connection Equipment No.       | 74             |

These fieldbus gateways allow an easy connection of sensors and scanners to Fast Ethernet.

**Complementary Products**

Software

