



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



Winstar Display Co., LTD

華凌光電股份有限公司



WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw

SPECIFICATION

MODULE NO.: TST0005R0F4111XXXX02

General Specification

Construction

Construction	Materials Used	Comment
COVER LENS	GLASS	Thickness : 1.10mm
SCA	Adhesive	Thickness : 0.20mm
ITO GLASS	ITO GLASS	Thickness : 0.70mm

Mechanical characteristics

Item	Description	Unit
Outside Dimension	147.00±0.10*104.00±0.10	mm
View Area	109.0±0.2*65.60±0.2	mm
Active Area	110.4±0.2*67.0±0.2	mm
Thickness	2.1±0.15 (With D.S.T)	mm
Input Method	Finger Or Conductive Pen	
Hardness Of Surface	Hard Surface : ≥7H	
Accuracy	±1mm@10mm	mm
Support Operation	Finger	Five-finger touch
Channel	11*18	
Interface	IIC	
Supported Operating Systems	Android2.0-4.2Windows	

Electrical Characteristics

Item	Description	Unit
Operating Voltage	2.8-3.3V	V
Chatting Times	<10ms	ms
FW	GVE7597A_COV_V65_ID0_LU_5F_800X480_230928.cfg	
FW Version	65	

Contour Drawing

