

WINSTAR Display

OLED SPECIFICATION


Model No:

WEP012864Q




General Specification

| Item | Dimension | Unit |
|------------------|--------------------------|------|
| Dot Matrix | 128 x 64 | — |
| Module dimension | 82.0 × 47.5 × 7 Max. | mm |
| Active Area | 61.41 × 30.69 | mm |
| Pixel Size | 0.45 × 0.45 | mm |
| Pixel Pitch | 0.48 × 0.48 | mm |
| Display Mode | Passive Matrix | |
| Display Color | Monochrome | |
| Drive Duty | 1/64 Duty | |
| OLED IC | SSD1309 | |
| OLED Interface | 6800,8080,4-Wire SPI,I2C | |
| Size | 2.7 inch | |

Contour Drawing & Block Diagram



| PIN | SYMBOL | PIN | SYMBOL | PIN | SYMBOL |
|-----|-----------|-----|--------|-----|--------|
| 1 | VSS | 9 | DB2 | 17 | CS# |
| 2 | VDD | 10 | DB3 | 18 | NC |
| 3 | NC | 11 | DB4 | 19 | BS2 |
| 4 | D/C# | 12 | DB5 | 20 | BS1 |
| 5 | R/W#(WR#) | 13 | DB6 | 21 | NC |
| 6 | E(/RD#) | 14 | DB7 | 22 | NC |
| 7 | DB0 | 15 | NC | 23 | NC |
| 8 | DB1 | 16 | RES# | 24 | NC |



The non-specified tolerance of dimension is ± 0.3 mm .

Interface Pin Function

| No. | Symbol | Function |
|------|------------|--|
| 1 | VSS | Ground. |
| 2 | VDD | Power supply pin for core logic operation |
| 3 | NC | No connection |
| 4 | D/C# | This pin is Data/Command control pin connecting to the MCU. When the pin is pulled HIGH, the data at D[7:0] will be interpreted as data. When the pin is pulled LOW, the data at D[7:0] will be transferred to a command register. In I2C mode, this pin acts as SA0 for slave address selection. |
| 5 | R/W# (WR#) | This pin is read / write control input pin connecting to the MCU interface. When 6800 interface mode is selected, this pin will be used as Read/Write (R/W#) selection input. Read mode will be carried out when this pin is pulled HIGH and write mode when LOW. When 8080 interface mode is selected, this pin will be the Write (WR#) input. Data write operation is initiated when this pin is pulled LOW and the chip is selected. When serial or I2C interface is selected, this pin must be connected to VSS. |
| 6 | E(RD#) | This pin is MCU interface input. When 6800 interface mode is selected, this pin will be used as the Enable (E) signal. Read/write operation is initiated when this pin is pulled HIGH and the chip is selected. When 8080 interface mode is selected, this pin receives the Read (RD#) signal. Read operation is initiated when this pin is pulled LOW and the chip is selected. When serial or I2C interface is selected, this pin must be connected to VSS. |
| 7-14 | D0~D7 | These pins are bi-directional data bus connecting to the MCU data bus. Unused pins are recommended to tie LOW. When serial interface mode is selected, D0 will be the serial clock input: SCLK; D1 will be the serial data input: SDIN and D2 should be kept NC. When I2C mode is selected, D2, D1 should be tied together and serve as SDAout, SDAin in application and D0 is the serial clock input, SCL. |
| 15 | NC | No connection |
| 16 | RES# | This pin is reset signal input. When the pin is pulled LOW, initialization of the chip is executed. Keep this pin pull HIGH during normal operation. |
| 17 | CS# | This pin is the chip select input connecting to the MCU. The chip is enabled for MCU communication only when CS# is pulled LOW (active LOW). |
| 18 | NC | No connection |

| | | | | | | | | | | | | | | | | | |
|---|-----|--|--|-----|-----|-----|---|---|---------------|---|---|---------------------|---|---|---------------------|---|---|
| 19 | BS2 | MCU bus interface selection pins. Select appropriate logic setting as described in the following table. BS2 and BS1 are pin select | | | | | | | | | | | | | | | |
| 20 | BS1 | <table border="1"><tr><td></td><td>BS1</td><td>BS2</td></tr><tr><td>I2C</td><td>1</td><td>0</td></tr><tr><td>4-wire Serial</td><td>0</td><td>0</td></tr><tr><td>8-bit 68XX Parallel</td><td>0</td><td>1</td></tr><tr><td>8-bit 80XX Parallel</td><td>1</td><td>1</td></tr></table> | | BS1 | BS2 | I2C | 1 | 0 | 4-wire Serial | 0 | 0 | 8-bit 68XX Parallel | 0 | 1 | 8-bit 80XX Parallel | 1 | 1 |
| | BS1 | BS2 | | | | | | | | | | | | | | | |
| I2C | 1 | 0 | | | | | | | | | | | | | | | |
| 4-wire Serial | 0 | 0 | | | | | | | | | | | | | | | |
| 8-bit 68XX Parallel | 0 | 1 | | | | | | | | | | | | | | | |
| 8-bit 80XX Parallel | 1 | 1 | | | | | | | | | | | | | | | |
| <p>Note</p> <p>(1) 0 is connected to VSS (2) 1 is connected to VDD</p> | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| 21 | NC | No connection | | | | | | | | | | | | | | | |
| 22 | NC | No connection | | | | | | | | | | | | | | | |
| 23 | NC | No connection | | | | | | | | | | | | | | | |
| 24 | NC | No connection | | | | | | | | | | | | | | | |

Absolute Maximum Ratings

| Parameter | Symbol | Min | Max | Unit |
|--------------------------|--------|------|-----|------|
| Supply Voltage for Logic | VDD | -0.3 | 4.0 | V |
| Operating Temperature | TOP | -40 | +80 | °C |
| Storage Temperature | TSTG | -40 | +85 | °C |

Electrical Characteristics

DC Electrical Characteristics

| Item | Symbol | Condition | Min | Typ | Max | Unit |
|-----------------------------------|---------|-----------|------------------|-----|------------------|------|
| Supply Voltage for Logic | VDD | — | 2.8 | 3.0 | 3.3 | V |
| High Level Input | VIH | — | $0.8 \times VDD$ | — | — | V |
| Low Level Input | VIL | — | — | — | $0.2 \times VDD$ | V |
| High Level Output | VOH | — | $0.9 \times VDD$ | — | — | V |
| Low Level Output | VOL | — | — | — | $0.1 \times VDD$ | V |
| 50% Check Board operating Current | VDD =3V | | — | 100 | 200 | mA |