

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



Winstar Display Co., LTD

華凌光電股份有限公司



WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw

SPECIFICATION

MODULE NO.: WF35NTVAJDNN0#

General Specifications

Item	Dimension	Unit
Size	3.5	inch
Dot Matrix	240 x 320	dots
Module dimension	62.9 x 86.54 x 4.1	mm
Active area	53.28 x 71.04	mm
Dot pitch	0.222 x 0.222	mm
LCD type	TFT, Normally Black, Transmissive	
View Direction	Wide View	
Aspect Ratio	Portrait	
Gray Scale	16 Gray scale (4BPP)/ 4 Gray scale (2BPP)/ 2 Gray scale (1BPP)	
Driver IC	ST7511	
Backlight Type	LED, Normally White	
Touch Panel	Without Touch Panel	
Surface	Glare	

* Mono tone slight changed by temperature and driving voltage.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-30	—	+80	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

1. Operating conditions:

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage For LCM	VDD	—	3.0	3.3	3.6	V
Supply Current For LCM	IDD	—	—	13	—	mA
Power Consumption	—	—	—	—	46.8	mW

2. LED driving conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit
LED current		—	160	—	mA
Power Consumption		—	—	—	mW
LED voltage	A-K	2.8	3.0	3.3	V
LED Life Time		50,000		—	Hr

Interface

1. LCM PIN Definition

Pin	Symbol	Function
1	GND	System ground
2	VDD	Power Supply : +3.3V
3	NC	No connect
4	A0	Data/Command select
5	/WR(R/W)	Write strobe signal
6	/RD(E)	Read strobe signal
7	DB0	Data bus
8	DB1	Data bus
9	DB2	Data bus
10	DB3	Data bus
11	DB4	Data bus
12	DB5	Data bus
13	DB6	Data bus
14	DB7	Data bus
15	/CS	Chip select
16	/RESET(RSTB)	Hardware reset
17	IF0	Mode select
18	IF1	
19	A	LED +
20	K	LED -
21	NC	No connect
22	NC	No connect

Contour Drawing

