

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



SPECIFICATION

MODULE NO.: WFN0400A2T0YAMNN000

General Specifications

Item	Dimension	Unit
Size	4.0	inch
Dot Matrix	720 x RGB x 720 (TFT)	dots
Module dimension	105.3 x 109.62 x 2.3	mm
Active area	101.52 x 101.52	mm
Pixel pitch	0.141 x 0.141	mm
LCD type	TFT, Normally Black, Transmissive	
Viewing Angle	85/85/85/85	
TFT Interface	4-Lanes MIPI	
Backlight Type	LED, Normally White	
TFT Driver IC	FL7703 or Equivalent	
Touch Panel	Without Touch Panel	
Surface	Anti-Glare	

*Color tone slight changed by temperature and driving voltage.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

1. Operating conditions

VCI=3.3V , GND=0V , Ta = 25 °C

Item		Symbol	Min.	Typ.	Max.	Unit
Digital supply Voltage		IOVCC	1.65	1.8	3.3	V
Analog supply Voltage		VCI	2.8	3.0	3.3	V
Input Signal Voltage	Low Level	VIL	0	-	0.3 x IOVCC	V
	High Level	VIH	0.7 x IOVCC	-	IOVCC	V
Current of digital supply voltage		IIOVCC	-	15	20	mA
Current of analog supply voltage		IVCI	-	35	50	mA

2. LED driving conditions

Item	Symbol	Min.	Typ.	Max.	Unit
LED current	-	-	40	45	mA
LED voltage	VLED+		15.5	16.0	V
Backlight Power Consumption	WBL	-	600	720	mW
LED Life Time	-	30,000	-	-	Hr


Interface

1. LCM PIN Definition

Match connector: XF2M-3015-1A (OMRON) or equivalent.

Pin No	Symbol	Description
1	VLED+	LED Anode
2	VLED-	LED Cathode1
3	VLED-	LED Cathode2
4	VCI	Power Supply 2.8V
5	IOVCC	LCD I/O power supply(1.8V)
6	RESET	Reset pin
7	TE	Tearing effect(1.8V)
8	NC	No connection.
9	GND	Ground
10	D0P	MIPI DSI differential data pair (Data lane 0)
11	D0N	MIPI DSI differential data pair (Data lane 0)
12	GND	Ground
13	D1P	MIPI DSI differential data pair (Data lane 1)
14	D1N	MIPI DSI differential data pair (Data lane 1)
15	GND	Ground
16	CLKP	MIPI DSI differential clock pair
17	CLKN	MIPI DSI differential clock pair
18	GND	Ground
19	D2P	MIPI DSI differential data pair (Data lane 2)
20	D2N	MIPI DSI differential data pair (Data lane 2)
21	GND	Ground
22	D3P	MIPI DSI differential data pair (Data lane 3)
23	D3N	MIPI DSI differential data pair (Data lane 3)
24	GND	Ground
25-30	NC	No connection.

Contour Drawing



The non-specified tolerance of dimension is $\pm 0.3 \text{ mm}$.