



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司

SPECIFICATION

MODEL NO. : WLOF00101000JGAACSA00

Summary

10.1 Inch Smart Display (Custom CAN ID series) Features


1. +12V power supply input, the power consumption is around 6W.
2. Self testing after booting function.
3. CAN bus communication interface.
4. Supports Custom CAN ID protocol. Default baud rate is at 250KB.
5. Built in 16MB flash memory, store the font and Object Dictionary Data.
6. Support capacitive touch panel (CTP).
7. Embedded buzzer controlled by Master Device.
8. Demo set HOST can be used on multiple platforms, such as Computer (with USB to CAN Dongle), MCU, Raspberry Pi (with PiCAN2).

Product information

General information

Item	Standard Value	Unit
Operating voltage	8V~28V dynamic	Vdc
Communication Interface	CAN bus differential ± 3.3	Vpp
MCU	STM32F746	N/A
Flash Memory	16	MB
SDRAM Frequency	166	MHz
LCD display size	10.1	inch
Dot Matrix	1024 x RGBx600(TFT)	dot
Module dimension	235(W) x 143(H) x 8.78(D)	mm
Active area	222.72 (H) x 125.28(V)	mm
Dot pitch	0.2175(W) x 0.2088(H)	mm
Brightness	Min:300; Typ:400	
LCD type	TFT, Normally Black, Transmissive	
View Direction	85/85/85/85	
Aspect Ratio	16:9	
Touch Panel	With CTP	
Surface	Glare	

Contour Drawing



Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage	VCC	—	8	12	28	V
Supply LCM current	I(mA)	-	-	530	-	mA

BOM

Item	Description
LCM	WF101JTYAHLNB0#
PCBA	SV10010R100JB00N0100

Interface

CON1 definition:

Pin	Symbol	Function	Remark
1	+12V	Power supply 12V input	Input
2	GND	Power supply GND input	Input
3	CAN_H	CAN bus D+	I/O
4	CAN_L	CAN bus D-	I/O
5	GND	Power supply GND input	GND
6	GND	Power supply GND input	GND
7	Reserve	USB_D-	Reserve
8	Reserve	USB_D+	Reserve
9	NC	-	-
10	Reserve	USART RX interface(Reserve)	Reserve
11	Reserve	USART TX interface(Reserve)	Reserve
12	GND	Power supply GND input	GND
13	+12V	Power supply 12V input	Input
14	NC	-	-
15	NC	-	-
16	GND	Power supply GND input	Input

CON2 definition:

Pin	Symbol	Function	Remark
1	VDD3V	3.3V power for JTAG interface	Output
2	JTAG_SWCLK	CLK pin for JTAG interface	Input
3	GND	GND for JTAG interface	Output
4	JTAG_SWDIO	Data pin for JTAG interface	I/O
5	NRST	Reset pin for JTAG interface	Input
6	GND	GND	Output
7	Wkup/ IO_8	(PA0) for system Resume from suspend (Reserve)	WKup,ADC,Timer,Event,I/O
8	/RST	Reset (active Low)	I
9	IO_0	ADC,DAC,Timer,Event,I/O	PA5
10	IO_1	ADC,Timer,Event,I/O	PA6
11	IO_2	ADC,Timer,Event,I/O	PA7
12	IO_3	RST,Timer,Event,I/O	PA8
13	IO_4	RST,Timer,Event,I/O	PC13
14	IO_5	ADC,Timer,Event,I/O	PB11
15	IO_6	RST,Timer,Event,I/O	PA15
16	IO_7	RST,ADC,Event,I/O	PD11