

Product data sheet  
Characteristics

## 9007AW12M11

Limit switch, 9007, 600 VAC 15amp aw  
+options

## Main

Range of product	9007
Series name	Heavy duty
Product or component type	Limit switch
Device short name	9007AW
Body type	Standard

## Complementary

Operator profile	Rotary head
Material	Metal
Body material	Cast zinc
Operator material	Cast zinc
Movement of operating head	Rotary
Type of operator	Spring return lever arm Momentary to be ordered separately
Switch actuation	CCW
Electrical connection	1...2 cables for screw-clamp terminals (AWG 22...AWG 12)
Cable entry	Conduit entry, cable outer diameter: 20 mm
Contacts type and composition	NC-NO, switch function: SPDT-DB
Contact form	Form Z
Contact operation	Snap action
Number of steps	1
Contacts material	Silver contacts
Positive opening	Without
Terminals description ISO n°1	(1-2)NC (3-4)NO
Minimum torque for tripping	0.31 N.m
Tripping angle	2.5 °
Maximum displacement angle	30 °
[Ie] rated operational current	15 A at 120 V AC, A600 conforming to NEMA rating designation
[Ithe] conventional enclosed thermal current	15 A
[Ui] rated insulation voltage	600 V conforming to UL 508 for contact block
Width	68.33 mm
Height	93.47 mm
Depth	36.58 mm
Net weight	0.57 kg
Product certifications	UL listed file E42259 CCN NKCR[RETURN]CE[RETURN]CSA LR25490 class 3211 03

## Environment

NEMA degree of protection	NEMA 1/2/4/12/13 conforming to Nema type 250
IP degree of protection	IP65 conforming to IEC 60529
Ambient air temperature for operation	-51...85 °C
Ambient air temperature for storage	-51...85 °C
Protective treatment	Epoxy powder coat
Mounting location	Rear Front

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	45.161 cm
Package 1 Width	17.78 cm
Package 1 Length	114.709 cm
Package 1 Weight	566.991 g

## Offer Sustainability

Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
For all Reach Rohs enquiries contact us at	<a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>