



Main

Body type	Deep box
Device short name	AW
Series name	Heavy duty

Complementary

[In] rated current	10 A
Body material	Cast zinc
Contact form	Form ZZ DPDT-DB
Contact operation	Snap action
Contacts type and composition	2 NO/2 NC
Fluid connection type	0.5 inch BSP conduit entrance
Maximum displacement angle	30 °
Switch actuation	CCW
Tilting angle	5 °
Torque value	0.31 N.m
Tripping angle	2.5 °

Environment

Ambient air temperature for operation	-51...85 °C
NEMA degree of protection	NEMA 1/2/4/12/13
Product certifications	CSA LR25490 class 3211 03[RETURN]CE[RETURN]UL listed file E42259 CCN NKCR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.318 cm
Package 1 Width	7.112 cm
Package 1 Length	13.208 cm
Package 1 Weight	566.991 g

Offer Sustainability

Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com