

9007C52DM11

Limit switch, 9007, 9007C compact 1 NO/NC,
top roller plunger

Main

| | |
|-------------------------------|--|
| Range of product | 9007 |
| Series name | Heavy duty |
| Product or component type | Limit switch |
| Product specific application | Compact box |
| Device short name | 9007C |
| Body type | Plug-in |
| Head type | Plunger head |
| Material | Metal |
| Fixing mode | By the body |
| Movement of operating head | Linear |
| Type of operator | Steel spring return roller plunger (-) |
| Switch actuation | By 30° cam |
| Type of approach | Lateral approach, 2 directions |
| Electrical connection | Screw-clamp terminals (AWG 22...AWG 12), 1...2 |
| Cable entry | 1 entry for M20 x 1.5 mm conforming to BS 4568 |
| Number of poles | 1 |
| Contacts type and composition | NC-NO |
| Contact operation | Snap action |
| Positive opening | Without |
| Sale per indivisible quantity | 1 |

Complementary

| | |
|--|--|
| Body material | Zinc |
| Head material | Zinc |
| Function available | - |
| Switch function | SPDT-DB |
| Contact form | Form Z |
| Contacts material | Silver contacts |
| Terminals description ISO n°1 | (1-2)NC (3-4)NO |
| Minimum force for tripping | 3 lbf |
| Repeat accuracy | +/- 0.001 in linear travel of cam |
| [Ie] rated operational current | 1.2 A at 600 V AC, A600 conforming to NEMA 1.5 A at 480 V AC, A600 conforming to NEMA 3 A at 240 V AC, A600 conforming to NEMA 6 A at 120 V AC, A600 conforming to NEMA 0.1 A at 600 V DC, Q600 conforming to NEMA 0.27 A at 250 V AC, Q600 conforming to NEMA 0.55 A at 125 V DC, Q600 conforming to NEMA |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 600 V (pollution degree 3) conforming to UL 508 for contact block 600 V (pollution degree 3) conforming to CSA C22.2 No 14 for contact block |
| [Uiimp] rated impulse withstand voltage | 2.5 KV AC 1 min conforming to CE 2.2 KV AC 1 min conforming to UL 2.64 KV AC 1 s conforming to CSA |
| Short-circuit protection | 10 A by CC fuse, protection type: non-time delay |
| Electrical durability | 1000000 cycles |

| | |
|-----------------------|-----------------|
| Local signalling | without |
| Mechanical durability | 10000000 cycles |
| Width | 39.37 mm |
| Height | 96.01 mm |
| Depth | 45.47 mm |
| Net weight | 0.57 kg |

Environment

| | |
|---------------------------------------|---|
| Shock resistance | 60 gn for 9 ms conforming to IEC 60068-2-27 |
| Vibration resistance | 25 gn (f= 10...150 Hz) conforming to IEC 60068-2-6 |
| NEMA degree of protection | NEMA 1 conforming to Nema type 250 NEMA 2 conforming to Nema type 250 NEMA 4 conforming to Nema type 250 NEMA 6 conforming to Nema type 250 NEMA 6P conforming to Nema type 250 NEMA 12 conforming to Nema type 250 NEMA 13 conforming to Nema type 250 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| Electrical shock protection class | Class 0 conforming to IEC 61140 |
| Ambient air temperature for operation | -29...85 °C for standard environment |
| Ambient air temperature for storage | -20...185 °F |
| Environmental characteristic | Standard environment |
| Protective treatment | Epoxy powder coat |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.064 cm |
| Package 1 Width | 5.08 cm |
| Package 1 Length | 13.208 cm |
| Package 1 Weight | 566.991 g |

Offer Sustainability

| | |
|--|---|
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|