



Main

Range of product	9007
Series name	Heavy duty
Head type	Rotary head
Type of operator	spring return lever arm (standard pre-travel) (to be ordered separately)
Switch actuation	CW
Cable entry	NPT conduit entry, cable outer diameter: 12.7 mm
Contacts type and composition	1 NO/1 NC
Contact operation	Snap action

Complementary

Body material	Zinc alloy
Switch function	SPDT-DB
Contact form	Form Z
Contacts material	Silver alloy (Ag/Ni)
Minimum torque for tripping	0.5 N.m
[Ie] rated operational current	10 A, A600 10 A, Q600
[Ui] rated insulation voltage	600 V
Local signalling	without
Product certifications	CE[RETURN]UL listed[RETURN]CSA
Provided equipment	Receptacle

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.318 cm
Package 1 Width	7.112 cm
Package 1 Length	10.922 cm
Package 1 Weight	600.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	12.446 cm
Package 2 Width	14.732 cm
Package 2 Length	22.86 cm
Package 2 Weight	5.729 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com