



**Main**

Range of product	9007
Series name	Heavy duty
Device short name	C
Head type	Plunger head
Type of operator	Spring return side roller plunger
Switch actuation	Horizontal
Cable entry	NPT conduit entry, cable outer diameter: 12.70 mm
Contacts type and composition	1 NO/1 NC
Contact operation	Snap action
Operating distance	0.25 inch
Operating travel	0.76 Mm 2.03 mm

**Complementary**

Body material	Zinc alloy
Switch function	SPDT-DB
Contact form	Form Z
Contacts material	Silver alloy (Ag/Ni)
[Ie] rated operational current	10 A, A600 10 A, Q600
[Ui] rated insulation voltage	600 V
Product certifications	UL listed[RETURN]CE[RETURN]CSA
Provided equipment	Receptacle

**Environment**

Ambient air temperature for operation	-18...85 °C
---------------------------------------	-------------

**Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.419 cm
Package 1 Width	10.795 cm
Package 1 Length	69.645 cm
Package 1 Weight	566.991 g

**Offer Sustainability**

Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
For all Reach Rohs enquiries contact us at	<a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>