



Main

Range of product	9007
Series name	Heavy duty
Product or component type	Limit switch plug-in unit
Device short name	9007C
Local display	Without
Contacts type and composition	NC-NO
Contact operation	Snap action

Complementary

Body material	Zinc alloy
Switch actuation	CW and CCW
Switch function	SPDT-DB
Contact form	Form Z
Contacts material	Silver alloy (Ag/Ni)
[Ie] rated operational current	10 A at 120 V AC, A600
[Ui] rated insulation voltage	600 V conforming to CE 600 V conforming to CSA 600 V conforming to UL 508
Terminals description ISO n°1	(3-4)NO (1-2)NC
Width	39.37 mm
Height	79.76 mm
Depth	45.47 mm
Net weight	0.57 kg
Head type	Rotary head
Provided equipment	Without receptacle
Specificity of operator	Standard pre-travel
Torque value	0.5 N.m
Type of operator	Spring return lever arm to be ordered separately

Environment

Vibration resistance	25 gn (f= 10...150 Hz) conforming to IEC 60068-2-6
NEMA degree of protection	NEMA 1/2/4X/6/6P/12/13 conforming to Nema type 250
IP degree of protection	IP67 conforming to IEC 60529
Electrical shock protection class	Class 0 conforming to IEC 61140
Ambient air temperature for storage	-20...185 °F
Protective treatment	Epoxy powder coat

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.806 cm
Package 1 Width	10.16 cm
Package 1 Length	65.548 cm
Package 1 Weight	371.946 g

Offer Sustainability

Sustainable offer status	Green Premium product
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com