

# 9013FHG12J55M1X

Pumptrol, air compressor switch 9013FH, fixed differential, Off at 150 PSI, low hp



## Main

|                              |                                                   |
|------------------------------|---------------------------------------------------|
| Range of product             | Pumptrol                                          |
| Pressure sensor name         | 9013FH                                            |
| Pressure sensor size         | 1034.21 kPa                                       |
| Value of setting             | Off at 150 psi                                    |
| Electrical circuit type      | Power circuit                                     |
| Product specific application | Control small electrically driven air compressors |
| Quantity per set             | 1                                                 |
| Type of packing              | Individual                                        |

## Complementary

|                                     |                                                                                                                                                                                                                                          |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pressure sensor type                | Electromechanical pressure switch                                                                                                                                                                                                        |
| Controlled fluid                    | Air (-0...70 °C)                                                                                                                                                                                                                         |
| Adjustable range on rising pressure | 482.6...1034.2 kPa                                                                                                                                                                                                                       |
| Approximate fixed differential      | 206.8 kPa                                                                                                                                                                                                                                |
| Destruction pressure                | 1516.8 kPa                                                                                                                                                                                                                               |
| Pressure actuator                   | Diaphragm                                                                                                                                                                                                                                |
| Pressure switch type of operation   | Regulation between 2 thresholds                                                                                                                                                                                                          |
| Scale type                          | Fixed differential                                                                                                                                                                                                                       |
| Setting                             | Internal                                                                                                                                                                                                                                 |
| Local display                       | Without                                                                                                                                                                                                                                  |
| Contacts type and composition       | 2 NC, snap action, DPST-DB, Form YY                                                                                                                                                                                                      |
| Cable entry number                  | 2 22.35 mm cable entries with 0.84 in across flats conforming to UL 508                                                                                                                                                                  |
| Electrical connection               | Screw-clamp terminals, clamping capacity: 10 AWG<br>Screw-clamp terminals, clamping capacity: 5.261 mm <sup>2</sup>                                                                                                                      |
| Fluid connection type               | 0.25 inch NPSF internal conforming to UL 508                                                                                                                                                                                             |
| Short-circuit protection            | 20 A cartridge fuse, type gG                                                                                                                                                                                                             |
| Materials in contact with fluid     | Zinc plated steel or equivalent flange<br>Nitrile (Buna-N) or equivalent rubber diaphragm                                                                                                                                                |
| Material                            | Polypropylene: cover<br>Noryl thermoplastic resin or equivalent: cover                                                                                                                                                                   |
| Operating position                  | Any position                                                                                                                                                                                                                             |
| Motor power kW                      | 1.1 KW (1.5 hp) at 115 V AC, 1 phase<br>1.5 KW (2 hp) at 230 V AC, 1 phase<br>1.5 KW (2 hp) at 115 V AC, 3 phases<br>2.2 KW (3 hp) at 230 V AC, 3 phases<br>0.75 KW (1 hp) at 460 V AC, 3 phases<br>0.75 kW (1 hp) at 575 V AC, 3 phases |
| Electrical durability               | 100000 cycles, operating rate <10 cyc/mn                                                                                                                                                                                                 |
| Mechanical durability               | 300000 cycles                                                                                                                                                                                                                            |
| Terminal block type                 | 4 terminals                                                                                                                                                                                                                              |
| Maximum operating rate              | 10 cyc/mn                                                                                                                                                                                                                                |
| [Ui] rated insulation voltage       | 575 V conforming to UL 508                                                                                                                                                                                                               |
| Net weight                          | 0.5 kg                                                                                                                                                                                                                                   |
| Repeat accuracy                     | +/- 3 %                                                                                                                                                                                                                                  |
| Terminals description ISO n°1       | L1-T1<br>L2-T2                                                                                                                                                                                                                           |
| Width                               | 78.74 mm                                                                                                                                                                                                                                 |

|                      |                                                                            |
|----------------------|----------------------------------------------------------------------------|
| Height               | 94.23 mm                                                                   |
| Depth                | 95.50 mm                                                                   |
| Factory modification | Maintained manual cut-out lever (AUTO-OFF)<br>2-way pressure release valve |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Standards                             | UL 508<br>CE                 |
| Ambient air temperature for operation | -22...158 °F                 |
| Ambient air temperature for storage   | -22...158 °F                 |
| Protective treatment                  | None                         |
| NEMA degree of protection             | NEMA 1 conforming to UL 50   |
| IP degree of protection               | IP20 conforming to IEC 60529 |
| Product certifications                | CSA[RETURN]UL listed         |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 10.2 cm |
| Package 1 Width              | 9.7 cm  |
| Package 1 Length             | 10.4 cm |
| Package 1 Weight             | 394.6 g |

## Offer Sustainability

|                                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>                                                                                                                                                                                                                                                                                                    |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|