



Main

Device short name	FHG
Enclosure type	Standard environment enclosure for indoor
Product specific application	Control small electrically driven air compressors
Quantity per set	Set of 20
Range of product	Square D Pumptrol

Complementary

Adjustable range on rising pressure	275.79...689.48 kPa
Approximate fixed differential	137.90 kPa
Contact code designation	A600
Depth	70.61 mm
Device composition	Black cover
Electrical connection	Screw clamp terminal
Fixing mode	By brackets
Fluid connection type	0.25 inch NPSF internal
Height	71.1 mm
Materials in contact with fluid	Nitrile (Buna-N) diaphragm
Maximum pressure	220 psig
Motor power hp	1 Hp at 460/575 V AC, 3 phases 2 Hp at 115 V AC, 1 phase 3 Hp at 115 V AC, 3 phases 3 Hp at 230 V AC, 1 phase 5 hp at 230 V AC, 3 phases
Number of poles	2
Permissible voltage	575 V AC
Pressure actuator	Diaphragm
Pressure setting range	689.48 kPa off
Net weight	0.51 kg
Scale type	Fixed differential
Switch function	DPST
Width	95.50 mm

Environment

NEMA degree of protection	NEMA 1
Product certifications	UL listed file E12158 CCN NKPZ[RETURN]CSA LR25490 class 3211 06

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.098 cm
Package 1 Width	37.084 cm
Package 1 Length	20.574 cm
Package 1 Weight	453.592 g

Offer Sustainability

California proposition 65

WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

For all Reach Rohs enquiries contact us at

sustainability@tesensors.com