



#### Main

|                              |                                         |
|------------------------------|-----------------------------------------|
| Range of product             | Pumptrol                                |
| Pressure sensor name         | 9013FS                                  |
| Pressure sensor size         | 448.16 kPa (34.47...310.26 kPa)         |
| Value of setting             | 30...50 psi                             |
| Electrical circuit type      | Power circuit                           |
| Product specific application | Control electrically driven water pumps |
| Quantity per set             | 1                                       |
| Type of packing              | Individual                              |

#### Complementary

|                                     |                                                                                                                                                                                                                                          |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pressure sensor type                | Electromechanical pressure switch                                                                                                                                                                                                        |
| Controlled fluid                    | Fresh water (-0...70 °C)                                                                                                                                                                                                                 |
| Adjustable range on rising pressure | 137.9...448.2 kPa                                                                                                                                                                                                                        |
| Approximate adjustable differential | 103.4...206.8 kPa                                                                                                                                                                                                                        |
| Destruction pressure                | 1516.8 kPa                                                                                                                                                                                                                               |
| Pressure actuator                   | Diaphragm                                                                                                                                                                                                                                |
| Pressure switch type of operation   | Regulation between 2 thresholds                                                                                                                                                                                                          |
| Scale type                          | Adjustable differential                                                                                                                                                                                                                  |
| Setting                             | Internal                                                                                                                                                                                                                                 |
| Local display                       | Without                                                                                                                                                                                                                                  |
| Contacts type and composition       | 2 NC, snap action, DPST-DB, Form YY                                                                                                                                                                                                      |
| Cable entry number                  | 2 22.35 mm cable entries with 0.84 in across flats conforming to UL 508                                                                                                                                                                  |
| Electrical connection               | Screw-clamp terminals, clamping capacity: 10 AWG<br>Screw-clamp terminals, clamping capacity: 5.261 mm <sup>2</sup>                                                                                                                      |
| Fluid connection type               | 0.25 inch NPT external conforming to UL 508                                                                                                                                                                                              |
| Short-circuit protection            | 20 A cartridge fuse, type gG                                                                                                                                                                                                             |
| Materials in contact with fluid     | Zinc plated steel or equivalent flange<br>Nitrile (Buna-N) or equivalent rubber diaphragm                                                                                                                                                |
| Material                            | Polypropylene: cover<br>Noryl thermoplastic resin or equivalent: cover                                                                                                                                                                   |
| Operating position                  | Any position                                                                                                                                                                                                                             |
| Motor power kW                      | 1.1 KW (1.5 hp) at 115 V AC, 1 phase<br>1.5 KW (2 hp) at 230 V AC, 1 phase<br>1.5 KW (2 hp) at 115 V AC, 3 phases<br>2.2 KW (3 hp) at 230 V AC, 3 phases<br>0.75 KW (1 hp) at 460 V AC, 3 phases<br>0.75 kW (1 hp) at 575 V AC, 3 phases |
| Electrical durability               | 100000 cycles, operating rate <10 cyc/mn                                                                                                                                                                                                 |
| Mechanical durability               | 300000 cycles                                                                                                                                                                                                                            |
| Terminal block type                 | 4 terminals                                                                                                                                                                                                                              |
| Maximum operating rate              | 10 cyc/mn                                                                                                                                                                                                                                |
| [Ui] rated insulation voltage       | 575 V conforming to UL 508                                                                                                                                                                                                               |
| Net weight                          | 0.5 kg                                                                                                                                                                                                                                   |
| Repeat accuracy                     | +/- 3 %                                                                                                                                                                                                                                  |
| Terminals description ISO n°1       | L1-T1<br>L2-T2                                                                                                                                                                                                                           |
| Width                               | 70.61 mm                                                                                                                                                                                                                                 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                      |          |
|----------------------|----------|
| Height               | 71.1 mm  |
| Depth                | 95.50 mm |
| Factory modification | -        |

## Environment

|                                       |                                     |
|---------------------------------------|-------------------------------------|
| Standards                             | UL 508<br>NSF ANSI 61 Annex G<br>CE |
| Ambient air temperature for operation | -22...158 °F                        |
| Ambient air temperature for storage   | -22...158 °F                        |
| Protective treatment                  | None                                |
| NEMA degree of protection             | NEMA 1 conforming to UL 50          |
| IP degree of protection               | IP20 conforming to IEC 60529        |
| Product certifications                | UL listed[RETURN]CSA                |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 25.806 cm |
| Package 1 Width              | 10.16 cm  |
| Package 1 Length             | 65.548 cm |
| Package 1 Weight             | 371.946 g |
| Unit Type of Package 2       | CAR       |
| Number of Units in Package 2 | 50        |
| Package 2 Height             | 22.352 cm |
| Package 2 Width              | 38.862 cm |
| Package 2 Length             | 52.578 cm |
| Package 2 Weight             | 20.239 kg |

## Offer Sustainability

|                                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status                   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>                                                                                                                                                                                                                                                                                                    |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|