

Electromechanical vacuum switch, 9016G,  
adjustable scale, 2 thresholds, Set 0 to 28.3  
InHg



Main

Range of product	9016G
Product or component type	Electromechanical vacuum switch
Device application	Sensitive control application
Device short name	9016G
Electrical circuit type	Control circuit

Complementary

Factory modification	-
Vacuum switch type of operation	Regulation between two thresholds
Scale type	Adjustable differential
Value of setting	-
Vacuum sensor size	28.7 inHg
Range on decreasing vacuum	0...28.7 inHg
Approx adjustable differential at mid range	1.3...7.4 inHg
Maximum pressure	100 psi
Maximum permissible pressure - per cycle	689.5 kPa
Local display	Without
Fluid connection type	0.25 inch 18 NPTF conforming to UL 508
Electrical connection	Screw-clamp terminals AWG 22...AWG 12
Cable entry	0.5 inch NPT conduit entrance
Terminal block type	4 screw terminals
Pressure actuator	Diaphragm nitrile (Buna-N)
Controlled fluid	Air (-40...250 °F) Water (-40...250 °F) Hydraulic oil (-40...250 °F) Gas (-40...250 °F)
Materials in contact with fluid	Zinc plated steel Nitrile (Buna-N) 3M Scotch-Grip 847 rubber and gasket adhesive
Enclosure material	Die cast aluminium alloy 380
Operating position	Any position
Maximum operating rate	120 cyc/mn
Repeat accuracy	0.4 %
[In] rated current	3 A 240 V AC A600 conforming to NEMA rating designation 6 A 120 V AC A600 conforming to NEMA rating designation 0.27 A 250 V DC R300 conforming to NEMA rating designation 0.22 A 125 V DC R300 conforming to NEMA rating designation
Local signalling	Without:
Contacts type and composition	NC-NO, SPDT, Form Z, snap action, silver nickel contacts
Short-circuit protection	10 A cartridge overload and short-circuit protection, type gL
Mechanical durability	5000000 cycles
Setting	Internal
Net weight	2.09 kg

Height	163.83 mm
Depth	115.82 mm
Width	115.82 mm

## Environment

Standards	UL 508
Product certifications	UL listed[RETURN]CSA
Protective treatment	None
Ambient air temperature for operation	10...185 °F
Ambient air temperature for storage	10...185 °F
Vibration resistance	2 gn conforming to IEC 68-2-6 (f = 40...150 Hz)
Shock resistance	50 gn conforming to IEC 58-2-27
NEMA degree of protection	NEMA 4/4X/13 conforming to UL 698

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.24 cm
Package 1 Width	19.05 cm
Package 1 Length	19.304 cm
Package 1 Weight	1.982 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

## Contractual warranty

Warranty	18 months
----------	-----------