

Float switch, Pumptrol, open tank, NEMA 4, pedestal mounted, 2 NC DPST DB contacts



Main

Range of product	Pumptrol
Product or component type	Float switch
Device application	Open tank heavy duty
Device short name	9036G
Product specific application	Liquid level control
Electrical circuit type	Power circuit
Quantity per set	Set of 1
Type of packing	Individual

Complementary

Product destination	For open tank or sump
Device mounting	Pedestal
Cable entry number	2 conduit entries for 3/4"-14 NPT conforming to UL 508
Contacts type and composition	2 NC, snap action, DPST-DB, Form YY
Controlled fluid	Fresh water at specific gravity of 0.85 in or higher Sea water at specific gravity of 0.85 in or higher Hydraulic oil at specific gravity of 0.85 in or higher Corrosive fluid at specific gravity of 0.85 in or higher
Motor power kW	1.5 KW (2 hp) at 115 V AC, 1 phase 2.2 KW (3 hp) at 115 V AC, 3 phases 2.2 KW (3 hp) at 230 V AC, 1 phase 3.7 KW (5 hp) at 230 V AC, 3 phases 0.75 KW (1 hp) at 460 V AC, 3 phases 0.75 KW (1 hp) at 475 V AC, 3 phases 0.18 KW (0.25 hp) at 32 V DC, 3 phases 0.37 KW (0.5 hp) at 115 V DC, 3 phases 0.37 KW (0.5 hp) at 230 V DC 3.7 KW (5 hp) at 460 V AC, 1 phase 3.7 kW (5 hp) at 475 V AC, 1 phase
Electrical connection	Screw-clamp terminals, clamping capacity: 10 AWG
Contact operation	Contacts close on liquid rise
Float movement	Variable adjustable
Float position	Any
Float rod angle	Vertical
Force down to trip	27 Ozf long lever 29 Ozf medium lever 31 ozf short lever
Force up to trip	20 Ozf long lever 22 Ozf medium lever 24 ozf short lever
Short-circuit protection	20 A cartridge fuse, type gG
Local signalling	Without
Enclosure material	Cast aluminium
Operating position	Vertical position only
Electrical durability	100 cycles, operating rate <60 cyc/mn
Mechanical durability	300 cycles
Terminal block type	4 terminals
Maximum operating rate	60 cyc/mn
[Ui] rated insulation voltage	575 V conforming to UL 508
Net weight	4.00 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Terminals description ISO n°1	Line-load-load-line
Factory modification	Without
Kit composition	Rod and float are to be choosen in accessories Float switch

Environment

Standards	CE UL 508
Ambient air temperature for operation	-30...93 °C
Ambient air temperature for storage	-30...93 °C
NEMA degree of protection	NEMA 4 conforming to UL 50
Product certifications	UL listed[RETURN]CSA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	67.742 cm
Package 1 Width	26.67 cm
Package 1 Length	172.064 cm
Package 1 Weight	3.96 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	80
Package 2 Height	101.6 cm
Package 2 Width	91.44 cm
Package 2 Length	121.92 cm
Package 2 Weight	317.074 kg

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisonyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------