



Main

Device short name	A
Enclosure type	Standard environment enclosure for indoor
Product specific application	Mechanically alternating the operation of two pumps or motors
Switch application	Standard

Complementary

Electrical connection	Screw clamp terminal
Material	Stainless steel: float/rod Nitrile (Buna-N): seal ring
Motor power hp	3 Hp at 230 V AC, 1 phase 5 Hp at 230 V AC, 3 phases 1 Hp at 460/575 V AC, 3 phases 3 Hp at 115 V AC, 1 phase 2 hp at 115 V AC, 3 phases
Mounting support	Flange
Number of poles	2
Permissible voltage	575 V AC
Switch function	DPST

Environment

NEMA degree of protection	NEMA 1
---------------------------	--------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.871 cm
Package 1 Width	11.76 cm
Package 1 Length	75.872 cm
Package 1 Weight	2.132 kg

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com